



CONTENTS

1. Spring framework
2. Spring Boot
3. Hibernate
4. Rest API Services, Postman
5. JWT
6. Refresh JWT
7. Service Discovery(Eureka Server & Client)



Spring Framework

Spring is a lightweight framework.

Spring provides support to various frameworks such as Struts, Hibernate, Tapestry, EJB, JSF, etc.

The Spring framework comprises several modules such as IOC, AOP, DAO, Context, ORM, WEB MVC etc.

Advantages of Spring Framework

1. **Predefined Templates:** Spring provides templates for JDBC, Hibernate, JPA, etc., reducing the need for writing boilerplate code.
2. **Loose Coupling:** Dependency injection ensures loose coupling between components.
3. **Easy Testing:** Spring makes it easier to test applications without requiring a server.
4. **Lightweight:** Spring's POJO (Plain Old Java Object) implementation keeps it non-invasive and lightweight.
5. **Fast Development:** Dependency Injection and support for various frameworks facilitate rapid JavaEE application development.
6. **Powerful Abstraction:** Spring abstracts JavaEE specifications like JMS, JDBC, JPA, and JTA²³⁴⁵.




Spring Modules

The Spring framework comprises of many modules

- Core
- Beans
- Context
- Expression language
- AOP
- Aspects, Instrumentation
- JDBC
- ORM
- OXM
- JMS
- Transaction
- Web
- Servlet
- Struts



Spring Framework Runtime





Spring Boot

Spring Boot is a project that is built on the top of the Spring Framework. It is easy to set up, configure and run both simple and web-based applications.

It is a Spring module that provides the feature to the Spring Framework. RAD (Rapid Application Development).

Spring Boot is the combination of Spring Framework and Embedded Servers.

Spring Framework + Embedded HTTP Servers(Tomcat, Jetty) – XML<bean> Configuration or @Configuration = Spring Boot
--

Prerequisite of Spring Boot Features

- Java 1.8
- Maven 3.0+
- Spring Framework 5.0.0.BUILD-SNAPSHOT
- An IDE (Spring Tool Suite) is recommended.



Spring Boot Features

- Web Development
- Spring Application
- Application events and listeners
- Admin features
- Externalized Configuration
- Properties Files
- YAML Support
- Type-safe Configuration
- Logging
- Security



Spring Boot Initializr

In any web browser if we type <https://start.spring.io/>, we will get user interface of spring initializr



Project

☐ Gradle - Groovy

☐ Gradle - Kotlin

☒ Maven

Language

☒ Java

☐ Kotlin

☐ Groovy

Spring Boot

☒ 3.3.0 (SNAPSHOT)

☐ 3.3.0 (M1)

☐ 3.2.3 (SNAPSHOT)

☐ 3.2.2

☐ 3.1.9 (SNAPSHOT)

☐ 3.1.8

Project Metadata

Group

Artifact

Name

Description

Package name

Dependencies

[ADD DEPENDENCIES...](#) CTRL + B

No dependency selected



GENERATE CTRL + ⌘

EXPLORE CTRL + SPACE

SHARE...



Hibernate

Hibernate is an Object-Relational Mapping (ORM) tool which bridges gap between object oriented features of Java and relational database.

Hibernate maps Java objects to database tables and vice versa.

Advantages of Hibernate Framework

1. Open Source and Lightweight
2. Fast Performance
3. Database Independent Query
4. Automatic Table Creation
5. Simplifies Complex Joins.
6. Query Statistics and Database Status

How Does Hibernate Work?

- Hibernate abstracts away many low-level details, such as establishing database connections, writing CRUD (Create, Read, Update, Delete) operations, and handling transactions.
- It uses **annotations** or **XML configuration** to define the mapping between Java classes and database tables.
- When you perform operations on Java objects (such as saving, updating, or retrieving data), Hibernate translates these actions into SQL queries and manages the database interactions behind the scenes



JPA (Java Persistence API)

JPA (Java Persistence API)

Java Persistence API (JPA) is a Java specification that provides certain functionality and standard to ORM tools. The javax.persistence package contains the JPA classes and interfaces.

JpaRepository

JpaRepository is a JPA (Java Persistence API) specific extension of Repository. It contains the full API of CrudRepository and PagingAndSortingRepository. So it contains API for basic CRUD operations and also API for pagination and sorting.

Methods of JpaRepository

- a) save() → Saves the object in the database table
- b) findAll() → fetches all the records of table
- c) findById() → fetch a record by id
- d) deleteById() → delete a record by id



Restful API

A RESTful API, or simply a REST API, is a web service that follows the principles of Representational State Transfer (REST) architecture.

Features of Rest API

- a) Rest API is stateless, which means that the server does not store any information about the client's state. In the request itself all the information is included and server does not need to store any thing of client's information.
- b) Rest API is that it uses HTTP methods, such as GET, POST, PUT and DELETE, to indicate the type of operation the client requests.

GET request retrieves information from the server.

POST request is used to submit information to the server.

- c) REST API is that it is platform-independent, which means that it can be used with any programming language or framework that supports HTTP.



API Method

To create API methods using Java, our computer system should have following prerequisites

- Java Development Kit (JDK) 8 or later installed on your system.
- An Integrated Development Environment (IDE) like Eclipse or IntelliJ IDEA.
- Familiarity with Java programming, Spring and HTTP concepts.

Steps to create API methods

1. Set up the project.

The project can be set up by spring boot initializr.

In any web browser if we type <https://start.spring.io/>, we will get user interface of spring initializr.

In the spring initializr select java language and maven project.

2. Define the model

The object model is a system or interface which is basically used to visualize elements in terms of objects in a software application.

@Entity

```
public class Employee
{
    long empId,
    string empName,
    double salary
}
```

Inside the above class programmer need to write the setter and getter of properties of Employee class.



3. Implementing the repository

```
public interface EmployeeRepository extends JpaRepository<Employee, long>{}
```

4. Building the Service Layer

Service layer acts as a bridge between data access layer and controller layer.

```
public interface EmployeeService
```

```
{
```

```
    void updateEmployee(Employee employee);
```

```
}
```

```
public class EmployeeServiceImpl implements EmployeeService
```

```
{
```

```
    private final EmployeeRepository empRepository;
```

```
    @Override
```

```
    public void updateEmployee(Employee employee)
```

```
    {
```

```
        empRepository.save(employee);
```

```
    }
```

```
}
```



5. Creating Controller

@RestController

@RequestMapping("/api/employee")

public class EmployeeController

{

private final EmployeeService employeeService;

@PostMapping

public void saveEmployee(@RequestBody Employee employee)

{

employeeService.save(employee);

}

}

6. Setting database configuration in application.properties file.

Database Configuration

spring.jpa.properties.hibernate.dialect = org.hibernate.dialect.MySQL5Dialect

spring.datasource.url=jdbc:mysql://localhost:3306/employee_db?useSSL=false&allowPublicKeyRetrieval=true

spring.datasource.username=root

spring.datasource.password=dfT\$89*#@

Hibernate Properties

spring.jpa.hibernate.ddl-auto=update

spring.jpa.show-sql=true



Postman

Testing API Method

Postman is an API platform for building and using APIs.

Through postman API methods are tested.

The screenshot shows the Postman interface for a GET request to `http://localhost:8087/api/board/boards_list`. The request is saved and has 7 hidden headers. The Headers tab is active, showing the following headers:

Key	Value	Description
<input checked="" type="checkbox"/> Content-Type	application/json	
<input checked="" type="checkbox"/> Authorization	Bearer eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ2aXJhdCIsI...	
Key	Value	Description

The Body tab is active, showing the response in JSON format:

```
1 {
2   {
3     "boardId": 1,
4     "boardCode": "B01",
5     "boardName": "ICSE",
6     "returnMessage": null
7   },
8   {
9     "boardId": 2,
10    "boardCode": "B02",
11    "boardName": "CBSE",
12    "returnMessage": null
13  },
14  {
15    "boardId": 3,
16    "boardCode": "B03",
17    "boardName": "WB",
```

The status bar at the bottom indicates: Status: 200 OK, Time: 82 ms, Size: 606 B. There are buttons for 'Save as example' and 'Send'.



JWT (JSON Web Token)

JWT is an open standard for securely sharing JSON data between parties.

The data is encoded and digitally signed, which ensures its authenticity.

JWT is widely used in API authentication and authorization workflows, as well as for data transfer between clients and servers.

JWT provides secure way of transferring statements referred to as "claims" about an entity (typically the user) between two parties.

Claims in JWT are key-value pairs that are represented with either JWS (JSON Web Signature) or JWE (JSON Web Encryption).

JWS and JWE are standards for digitally signing and encrypting JWTs, which helps ensure their authenticity and integrity.

Structure of JWT

A JWT has three sections: a header, a payload, and a signature.

Each section is a Base64-encoded string, and the sections are separated by periods.

A typical JWT looks like this, where the X's represent the header, the Y's represents the payload, and the Z's represents the signature:

xxxxxx.yyyyyy.zzzzzz

xxxxxx → Header

yyyyyy → Payload

zzzzzz → Signature




Header: eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiIxMjM0NTY3ODkwIiwibmFtZSI6IjZ4RG91IiwiaWF0IjoxNTE2MjM5MDIyfQ.SflKxwRJSMeKKF2QT4fwpMeJf36P0k6yJV_adQssw5c

payload: Signature or encryption algorithm

signature

How does JWT gets created ?



As shown above user sends login request to the server from the client application.

API on the server end creates JWT.

JWT is returned to the client application from the server end.

From the client's end the further request is done with JWT attached.



Refresh JWT (JSON Web Token)

Refresh token is a unique token that is used to obtain additional access tokens and it is obtained without having to collect credentials every time one expires.



In the `application.properties` file we need to write properties for generation of token and refresh token

```
anodiam.app.jwtSecret= mySecretKey-123456jsfwwwrwsdfdsdsgsgeeeybvdgh
```

```
anodiam.app.jwtExpirationMs= 86400
```

```
anodiam.app.refreshExpirationDateInMs=9000000
```

```
anodiam.app.jwtRefreshExpirationMs=86400000
```



Spring boot – Eureka Server & Client

In order to communicate between services, the following components are required

- microservices architectures
- service registration
- discovery

Eureka Server is a service registry that plays a central role in the automatic detection of devices and services on a network. It acts as the heart of your microservices ecosystem, allowing service instances to register themselves and facilitating service discovery. Key aspects of Eureka Server include:

- Client Registration: Instances of microservices automatically register themselves with Eureka Server.
- Service Discovery: Eureka Server maintains a registry of all client applications running on different ports and IP addresses.

Eureka Server operates on a simple “Register, Lookup, Connect” principle, making it an excellent choice for managing microservices in a Spring Boot environment. Here are some compelling reasons to use Eureka Server:

1. Centralized Service Registry: Eureka Server knows about all client applications and their locations. This centralization simplifies service discovery.
2. Automatic Registration: Microservices automatically register themselves with Eureka Server, reducing manual configuration efforts.
3. Load Balancing: Eureka Server can help implement load balancing among service instances.
4. Health Checks: Eureka Server can perform health checks on registered services, ensuring robustness and reliability.
5. Integration with Spring Cloud: Eureka Server seamlessly integrates with the Spring Cloud ecosystem, enabling easy scaling and deployment.



In the java project's pom.xml on server and client side

```
<!-- For Eureka Server -->
```

```
<dependency>
```

```
  <groupId>org.springframework.cloud</groupId>
```

```
  <artifactId>spring-cloud-starter-netflix-eureka-server</artifactId>
```

```
</dependency>
```

```
<!-- For Eureka Client -->
```

```
<dependency>
```

```
  <groupId>org.springframework.cloud</groupId>
```

```
  <artifactId>spring-cloud-starter-netflix-eureka-client</artifactId>
```

```
</dependency>
```

To enable Eureka functionality, the programmer needs to enable annotation

@EnableEurekaServer: Use this annotation to designate a Spring Boot application as the central instance where other services will get registered.

@EnableEurekaClient: Services use this annotation to enable service registration and discovery with the central Eureka Server.



For marking a Spring Boot Application as an Eureka Server

```
@SpringBootApplication
```

```
@EnableEurekaServer
```

```
public class ServiceRegistryApplication {  
    public static void main(String[] args) {  
        SpringApplication.run(ServiceRegistryApplication.class, args);  
    }  
}
```

For marking a Spring Boot Application as an Eureka Client to be used up by the server

```
@SpringBootApplication
```

```
@EnableEurekaClient
```

```
public class StudentApplication {  
    public static void main(String[] args) {  
        SpringApplication.run(StudentApplication.class, args);  
    }  
}
```



Eureka Dashboard

When the Spring Boot application is up and running, just hit the default URL – <http://localhost:8761>.

Dashboard will display the list of micro services

The screenshot shows the Spring Eureka Dashboard in a Firefox browser window. The browser tabs include 'Eureka', 'Swagger UI', and two instances of 'localhost:8081/v3/api-docs'. The address bar shows 'localhost:8761'. The dashboard header features the 'spring Eureka' logo and navigation links for 'HOME' and 'LAST 3000 SINCE STARTUP'.

System Status

Environment	test	Current time	2023-07-08T01:48:48+0530
Data center	default	Uptime	00:09
		Lease expiration enabled	false
		Renews threshold	6
		Renews (last min)	6

EMERGENCY! EUREKA MAY BE INCORRECTLY CLAIMING INSTANCES ARE UP WHEN THEY'RE NOT. RENEWALS ARE LESSER THAN THRESHOLD AND HENCE THE INSTANCES ARE NOT BEING EXPIRED JUST TO BE SAFE.

DS Replicas

Instances currently registered with Eureka

Application	AMIs	Availability Zones	Status
API-GATEWAY	n/a (1)	(1)	UP (1) - 192.168.1.4:API-GATEWAY:8081
STUDENT-APP	n/a (1)	(1)	UP (1) - 192.168.1.4:STUDENT-APP:8080
TEACHER-APP	n/a (1)	(1)	UP (1) - 192.168.1.4:TEACHER-APP:8081

General Info

Name	Value
total-avail-memory	83mb
num-nodes	1

Dashboard of Eureka discovery client