

electron/gh-path.cjs

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:10:58.111Z

Overview

A new module `electron/gh-path.cjs` is added to resolve the GitHub CLI executable. It introduces `"use strict"` and imports `fssync`, `os`, `path`, and `spawnSync`. The module caches the resolved path in `cachedGhPath`.

Key changes

- **Imports** added at lines 3-6.
- `extraPathDirs` (lines 15-31) returns common bin directories: Homebrew, user-bin, and a Windows-specific `GitHub CLI` path.
- `augmentPathForCli` (lines 38-51) merges these dirs into the current `PATH`, deduplicating entries.
- `ghCandidatePaths` (lines 53-60) lists typical `gh` locations.
- `resolveViaLoginShell` (lines 63-90) runs `/bin/zsh` or `/bin/bash` with `-ilc / -lc` to locate `gh` on non-Windows systems.
- `verifyGh` (lines 92-98) executes `gh --version` to confirm the binary.
- `resolveGhExecutable` (lines 104-138) orchestrates the search: checks cache, candidate paths, login shell, then `which / where`; caches the result and falls back to `"gh"` or `"gh.exe"`.
- `clearGhCache` (lines 140-142) resets the cache.
- `isGhInstalled` (lines 144-150) verifies installation status.
- `ghInstallHint` (lines 152-160) returns platform-specific install guidance.
- `ghNotFoundError` (lines 162-164) creates an error containing the hint.
- **Exports** (lines 166-173) expose the public API.

Impact

- Centralizes `gh` resolution logic and caching, reducing repeated lookups.
- Provides actionable install hints in error messages.

Risks & follow-ups

- `augmentPathForCli` returns a new environment object; ensure it does not mutate the caller's `process.env`.
- `resolveViaLoginShell` depends on `/bin/zsh` or `/bin/bash`; if neither exists, the fallback must still locate `gh`.
- Cached path may become stale if `gh` is installed or removed during a session; `clearGhCache` should be invoked accordingly.
- Add unit tests for helpers, especially `ghCandidatePaths` and `ghInstallHint`, to guard against future changes.