

electron/git-blame.cjs

Kind: modified · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T17:31:41.503Z

Overview

`electron/git-blame.cjs` now supports blaming arbitrary Git refs via a new helper `blameFileAtRef`. The cache key and error payload were expanded to include the ref, and the module exports were updated.

Key changes

- Added `function blameFileAtRef(repoRoot, ref, relPath)` (lines 37-78) that accepts a Git ref and returns `{ lineAuthors, owners, ref, relPath, error }`.
- `blameFileOwnership` (lines 79-81) now delegates to `blameFileAtRef` with `"HEAD"`.
- Removed `cacheKey` (lines 8-11); cache key now `${root}::${gitRef}::${safeRelPath}` (line 44).
- `spawnSync` command now includes the ref argument before `--line-porcelain` (lines 50-56).
- Error objects now contain `ref`, `relPath`, and a trimmed `error` string (lines 59-65).
- Simplified type annotation for `blameCache` to `Map<string, object>` (line 5).
- Updated exports to `{ blameFileOwnership, blameFileAtRef, parseBlamePorcelain }` (lines 79-83).

Impact

- Enables blame queries on any commit, improving historical analysis.
- Cache now differentiates by ref, preventing stale data across branches.
- Error payload exposes `ref` and `relPath`, aiding debugging.

Risks & follow-ups

- Existing callers of `blameFileOwnership` remain functional, but any direct use of the old cache key format will break.
- Including ref in the key may increase cache entries; monitor memory usage.
- Callers must handle the new `error` field; update error-logging logic if necessary.
- Add unit tests for `blameFileAtRef` with non-HEAD refs to confirm cache isolation and error payload.