

## electron/github-auth-flow.cjs

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:13:41.506Z

### Overview

A new module `electron/github-auth-flow.cjs` (lines 1-141) implements a GitHub CLI device-code authentication flow. It exports `startGithubDeviceAuth`, `cancelGithubDeviceAuth`, and the constant `VERIFICATION_URI`.

### Key changes

- **Imports (lines 3-10):**
  - `spawn` from `node:child_process`
  - `shell` from `electron`
  - `augmentPathForCli`, `resolveGhExecutable`, `isGhInstalled`, `ghNotFoundError` from `./gh-path.cjs`
- **Utility (lines 17-20):** `stripAnsi` removes ANSI escape codes from CLI output.
- **Cancellation (lines 21-37):** `cancelGithubDeviceAuth` terminates any active `gh` child process ( `child.kill("SIGTERM")` at line 26) and clears `activeLogin`.
- **Auth flow (lines 38-141):**
  - Checks `gh` presence ( `isGhInstalled()` at line 41).
  - Spawns `gh auth login` with device-code flags (lines 51-58).
  - Parses output for a 4-segment code using `CODE_RE` (line 13).
  - Emits progress events ( `code`, `complete`, `error` ) via the supplied `emit` callback.
  - Opens the verification URL ( `shell.openExternal(VERIFICATION_URI)` at line 95).
  - Handles a 90s timeout (lines 73-77) and child process errors (lines 106-113).
  - On child close, emits `complete` or an error based on exit code (lines 115-131).
- **Exports (lines 137-141):** `startGithubDeviceAuth`, `cancelGithubDeviceAuth`, `VERIFICATION_URI`.

### Impact

- **Correctness:** Provides a clear, event-driven device-auth path that relies on `gh` being installed.
- **Maintainability:** Centralizes CLI path handling and error messaging; future flag changes can be made in one place.
- **Performance:** Minor overhead from spawning a child process; timeout is 90s.
- **Compatibility:** Requires Electron's `shell` API; not usable in non-Electron contexts.
- **Observability:** Emits detailed phases ( `code`, `complete`, `error` ) that can be logged or surfaced to the renderer.

### Risks & follow-ups

- **Regression risk:** Run session-regression tests targeting `startGithubDeviceAuth`.

- **CLI availability:** Verify `ghNotFoundError` surfaces correctly when `gh` is missing.
- **Lint & build:** Execute `npm run lint`, `npm test`, and the production build to catch syntax or type issues.
- **Shell integration:** Confirm `shell.openExternal` opens the correct URL on all supported platforms.