

electron/repo-discovery.cjs

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:18:32.783Z

Overview

A new module `electron/repo-discovery.cjs` is added to provide repository-discovery utilities for the Electron app, replacing previous ad-hoc logic.

Key changes

- **Imports** (diff lines 3-6): `node:fs`, `node:path`, `node:os`, and local helpers `parseGithubSlugFromUrl`, `tryRunGit`.
- **Constants** (lines 8-27): `SKIP_DIR_NAMES` set, `MAX_REPOS = 120`, `MAX_DEPTH = 4`.
- `homeSearchRoots()` (lines 29-68): builds candidate paths from the user's home directory, adds platform-specific ones, deduplicates, and returns only existing directories.
- `readGitRemoteSlug(repoRoot)` (lines 70-86): runs `git remote -v`, parses each line, and returns a slug object (`owner`, `repo`, `remote`, `url`) or `null`.
- `scanForGitRepos(roots, opts)` (lines 88-141): recursively walks each root up to `MAX_DEPTH`, stops after `MAX_REPOS` matches, skips ignored or hidden directories, and collects repo metadata (`path`, `name`, `slug`, `remoteUrl`).
- `discoverRepos(payload)` (lines 143-155): merges home roots with optional `extraRoots`, filters by target owner/repo, and returns `{ searchRoots, matches, scannedAt }`.
- `matchRepoForGithubRepo(owner, repo, extraRoots)` (lines 157-159): thin wrapper around `discoverRepos`.
- **Exports** (lines 161-166): `homeSearchRoots`, `discoverRepos`, `matchRepoForGithubRepo`, `readGitRemoteSlug`.

Impact

- Deterministic deduplication via a `seen` set; hidden/ignored directories are skipped; a target slug filter is applied (lines 92-120).
- All discovery logic is centralized; constants centralize limits (lines 26-27).
- Synchronous `fs` calls are bounded by `MAX_DEPTH` / `MAX_REPOS` (lines 95-97, 96-97).
- Uses Node 18
- `node:` import specifiers; may not work on older Electron/Node builds (diff lines 3-6).

Risks & follow-ups

- **Regression:** verify handling of permission errors and non-existent directories on Windows, Linux, macOS (lines 100-104, 106-110).
- **Compatibility:** test `node:` imports against the target Electron runtime; provide a fallback if necessary (diff lines 3-6).
- **Performance:** benchmark startup time on machines with many nested repos; consider async alternatives if blocking becomes an issue (unknown from the available diff/scan evidence).

- **Security:** synchronous file system access blocks the renderer thread; confirm acceptability for the app's UX (unknown from the available diff/scan evidence).