

## electron/workspace-store.cjs

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:20:21.010Z

### Overview

A new module `electron/workspace-store.cjs` is added to the Electron side of the repository. It implements a session and workspace persistence layer that replaces the previous ad-hoc storage logic.

### Key changes

- **Imports** (R3-R6): `fssync`, `fsp`, `path`, `randomUUID` bring in Node-core APIs for file I/O and UUID generation.
- **Path helpers** (R8-R14): `sessionPath(userData)` and `workspacesRoot(userData)` compute the locations for the session JSON and workspace directories.
- **JSON I/O** (R16-R31): `readJson` and `writeJson` use `fsp` to read/write JSON atomically via a temporary file.
- **Session CRUD** (R33-R52): `loadSession` loads the session or falls back to defaults; `saveSession` writes it back.
- **Workspace CRUD** (R74-R87, R89-R100, R103-R106): `upsertWorkspace`, `setActiveWorkspace`, `setGitUser`, `getWorkspace` manipulate the in-memory session and persist changes.
- **Live-repo update** (R108-R126): `updateWorkspaceLiveRepo` validates the path, updates the workspace, writes `meta.json`, and returns the updated session.
- **Workspace creation** (R128-R158): `createWorkspace` generates a UUID, resolves the repo root, creates data directories, writes `meta.json`, updates the session, and returns both objects.
- **Exports** (R161-R173): All public functions are exported for use by the renderer and other Electron modules.

### Impact

- **Atomic writes** via a temporary file ( `writeJson` uses `fsp.rename` ).
- **Fallback defaults** in `loadSession` provide a safe initial state.
- **Non-blocking I/O** with `fs/promises` and directory creation with `{ recursive: true }`.
- *\*Node 18+ requirement*
- ( `node:fs`, `node:crypto` ).

### Risks & follow-ups

- Verify that `loadSession` correctly handles missing or malformed files (fallback logic).
- Test concurrent calls to `createWorkspace` / `updateWorkspaceLiveRepo` for race conditions.
- Ensure `setLocalOnlyMode` clears `gitUser` and `activeWorkspaceId` as intended.

- Run the full lint, test, and production build pipeline to catch any import or path resolution issues.