

packages/graph-core/src/__tests__/layer-detector.test.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:10:17.027Z

Overview

A new test file `packages/graph-core/src/__tests__/layer-detector.test.ts` (lines R1-188) was added to exercise the layer-detection logic, prompt construction, response parsing, and LLM-based layer assignment.

Key changes

- **Imports** – `vitest` helpers and the four public functions from `../analyzer/layer-detector.js` were added (R1-R6).
- **Test helpers** – `makeNode` and `makeGraph` construct minimal `KnowledgeGraph` objects for the tests (R10-R32).
- **detectLayers tests** – verify detection of “API Layer”, “Data Layer”, and “Core” layers, unique kebab-case IDs, and that only nodes of type `file` are considered (R36-R106).
- **buildLayerDetectionPrompt test** – checks that file paths are included and the string “JSON” appears in the prompt (R109-R119).
- **parseLayerDetectionResponse tests** – cover plain JSON, JSON wrapped in markdown fences, and invalid inputs that should return `null` (R122-R160).
- **applyLLMLayers test** – ensures LLM-provided layers are applied correctly and unmatched nodes fall into an “Other” layer (R163-R188).

Impact

- **Coverage** – The tests exercise all stages of the layer-detection pipeline, reducing the risk of silent regressions.
- **Maintainability** – Centralized helper functions simplify future test additions.
- **Observability** – Failures will pinpoint the specific stage (e.g., prompt content or parsing logic) that broke.

Risks & follow-ups

- **Deterministic IDs** – Tests rely on node IDs; changes to ID generation could cause flakiness.
- **Prompt formatting** – If `buildLayerDetectionPrompt` changes, the test may need updating.
- **LLM contract** – `applyLLMLayers` assumes a specific layer shape; future LLM responses must match this contract.
- **Performance** – Running these tests on very large graphs could increase execution time; monitor if graph size grows.