

packages/graph-core/src/ignore-filter.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:40:11.007Z

Overview

A new file `packages/graph-core/src/ignore-filter.ts` (added in the diff) introduces a reusable ignore-filter. It exports:

- `DEFAULT_IGNORE_PATTERNS` (R9-R70) – a hard-coded list of common build, lock, binary, IDE, and license patterns.
- `IgnoreFilter` interface (R72-R75) with `isIgnored(relativePath: string): boolean`.
- `createIgnoreFilter(projectRoot: string)` (R86-R111) that builds an `ignore` instance, layers defaults, `.novadiff-graph/.novadiffignore`, and root `.novadiffignore`, then returns an object implementing `IgnoreFilter`.

Key changes

- **Imports:** added `ignore`, `readFileSync`, `existsSync`, and `join` (R1-R3).
- **Default patterns:** defined in `DEFAULT_IGNORE_PATTERNS` (R9-R70).
- **Interface:** `IgnoreFilter` (R72-R75).
- **Factory:** `createIgnoreFilter` (R86-R111) merges layers and exposes `isIgnored`.
- **Negation:** later patterns override earlier ones via `!` syntax, as noted in the comment block (R77-R84).

Impact

- Provides a single source for ignore rules that can be shared across scanning modules.
- Centralizes pattern maintenance; adding a rule requires editing only `DEFAULT_IGNORE_PATTERNS`.
- `ignore` parses patterns once per `createIgnoreFilter` call; subsequent `isIgnored` checks use `ig.ignore`, offering efficient lookups.
- No breaking API changes are introduced; the new module is additive.

Risks & follow-ups

- **Malformed ignore files:** `ignore` may silently ignore patterns; validate contents in tests.
- **Path resolution:** `join(projectRoot, ".novadiff-graph", ".novadiffignore")` assumes a fixed subdirectory; confirm it matches repository layout.
- **Negation precedence:** ensure later layers correctly override earlier ones; unit tests should cover `!` patterns.
- **Integration:** search for existing hard-coded ignore logic that may conflict; replace with `IgnoreFilter` where appropriate.