

packages/graph-core/src/ignore-generator.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:40:37.672Z

Overview

A new file `packages/graph-core/src/ignore-generator.ts` (added lines 1-3) introduces a helper to generate a starter `.novadiffignore`. The exported function `generateStarterIgnoreFile(projectRoot: string)` (lines 61-102) builds the file by collecting patterns from an existing `.gitignore`, detecting common directories, and suggesting generic test file patterns.

Key changes

- **Imports** – added `existsSync`, `readFileSync` from `node:fs` (R1), `join` from `node:path` (R2), and `DEFAULT_IGNORE_PATTERNS` from `./ignore-filter.js` (R3).
- **Constants** – `HEADER` (R5-7), `DETECTABLE_DIRS` (R15-26), and `GENERIC_SUGGESTIONS` (R28-32) define the file's structure.
- **Helper functions** –
 - `parseGitignorePatterns(gitignorePath)` (lines 37-44) reads a `.gitignore` and returns non-comment, non-blank lines.
 - `isCoveredByDefaults(pattern)` (lines 50-54) normalizes patterns and checks them against `DEFAULT_IGNORE_PATTERNS`.
- **Exported API** – `generateStarterIgnoreFile(projectRoot)` (lines 61-102) orchestrates three sections:
 1. Patterns from `.gitignore` that are not already covered by defaults.
 2. Detected directories from `DETECTABLE_DIRS`.
 3. Generic test file patterns from `GENERIC_SUGGESTIONS`.All suggestions are commented out (`# pattern`) and the function returns the joined string.

Impact

- Provides a deterministic starter ignore file, centralizing ignore logic.
- Adds negligible runtime cost: a single read of `.gitignore` and a small directory scan.
- No changes to existing public APIs; purely additive.

Risks & follow-ups

- **DEFAULT_IGNORE_PATTERNS** – verify that the import path resolves and the array contains the expected defaults.
- **Path resolution** – ensure `join(projectRoot, dir)` behaves correctly across OSes.
- **Comment syntax** – confirm downstream tooling respects the `#`-prefixed suggestions.

- **Test coverage** – unit tests for `generateStarterIgnoreFile` would guard against regressions in pattern filtering and directory detection.