

packages/graph-core/src/languages/catalog-builder.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:39:42.093Z

Overview

A new file `packages/graph-core/src/languages/catalog-builder.ts` is added.

It exports helpers that build `LanguageConfig` objects from the generated `alphabeticalCatalogEntries`.

Key changes

- **Imports (R1-R3)**
 - `LanguageConfig` from `./types.js`
 - `LanguageCatalogEntry` from `./catalog-types.js`
 - `alphabeticalCatalogEntries` from `./alphabetical-catalog.generated.js`
- **EMPTY_FILE_PATTERNS** (lines 5-10) supplies default empty arrays for `entryPoints`, `barrels`, `tests`, and `config`.
- **catalogEntryToLanguageConfig** (lines 12-27) converts a `LanguageCatalogEntry` to a `LanguageConfig`, copying `id`, `displayName`, `extensions`, and adding `filenames` and `treeSitter` when present.
- **buildAlphabeticalLanguageConfigs** (lines 29-31) maps all catalog entries to configs.
- **listAlphabeticalLanguages** (lines 33-45) returns a read-only array of `{ id, displayName, extensions, hasTreeSitter }` for UI use.

Impact

- Centralizes configuration construction; other modules can import the exported helpers.
- No changes to existing public APIs; the new helpers are additive.
- The implementation uses straightforward array mapping, so runtime cost is minimal for typical catalog sizes.

Risks & follow-ups

- Verify that `alphabeticalCatalogEntries` is correctly generated; missing entries would produce empty configs.
- Ensure `catalogEntryToLanguageConfig` handles optional `wasmsFile` and `filenames`; unit tests should cover edge cases.
- Confirm that `hasTreeSitter` flag matches downstream UI expectations.
- Run lint, tests, and production build to catch any type or import errors introduced by the new file.