

packages/graph-core/src/languages/framework-registry.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:40:47.473Z

Overview

A new file `packages/graph-core/src/languages/framework-registry.ts` (lines R1-86) introduces the `FrameworkRegistry` class, centralizing framework configuration handling.

Key changes

- **Imports (R1-R3)** – `FrameworkConfigSchema`, `FrameworkConfig` type, and `builtinFrameworkConfigs` are imported.
- **Class export (R9)** – `export class FrameworkRegistry` is added.
- **Internal maps (R10-R11)** – `byId` and `byLanguage` `Map`s store configurations.
- **register method (R13-R26)** – validates configs via `FrameworkConfigSchema`, skips duplicates, and indexes languages.
- **Lookup helpers (R28-R38)** – `getById`, `getForLanguage`, and `getAllFrameworks` expose read-only views.
- **detectFrameworks (R40-R74)** – scans a manifest map, matches filenames, and checks detection keywords case-insensitively.
- **Static factory (R76-R85)** – `createDefault` registers all `builtinFrameworkConfigs`.

Impact

- **Correctness** – Schema validation and duplicate guard prevent malformed or repeated entries.
- **Maintainability** – A single registry simplifies adding or updating framework configs.
- **Performance** – Map lookups and a single-pass detection keep runtime linear in the number of configs and manifests.
- **Observability** – No new logs; registry state can be inspected via public methods.

Risks & follow-ups

- `builtinFrameworkConfigs` must contain all expected entries; missing configs will silently fail detection.
- `detectFrameworks` performs case-insensitive keyword matching; test with mixed-case manifests to confirm.
- Duplicate registration is silently ignored; consider emitting a warning if needed.
- Run the existing test suite and linting to ensure imports and type resolution work.