

packages/graph-core/src/languages/language-registry.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:41:55.937Z

Overview

A new file `packages/graph-core/src/languages/language-registry.ts` introduces a `LanguageRegistry` class that stores language configurations and provides lookup by ID, file extension, or filename.

Key changes

- **Imports added** (R1-R6): `LanguageConfigSchema` , `LanguageConfig` , and helper functions from `./configs/index.js` .
- **LanguageRegistry class** (R12-R67):
 - Three `Map` s: `byId` , `byExtension` , `byFilename` .
 - `register(config)` parses with `LanguageConfigSchema` , normalizes extensions (adds a leading dot if missing), lower-cases filenames, and populates the maps.
 - Query helpers: `getById` , `getByExtension` , `getForFile` , `getAllLanguages` .
 - Static `createDefault()` builds a registry pre-loaded with all built-in configs via `languageConfigsForRegistry(detailedLanguageConfigs)` .

Impact

- **Centralized lookup:** all language config resolution is now in one place.
- **Performance:** `Map` gives O(1) lookups; extension normalization ensures consistent keys.
- **Maintainability:** registration logic is isolated, easing future updates.
- **Compatibility:** the new file is additive; no existing APIs are changed, so current code should compile unchanged.

Risks & follow-ups

- Verify that `languageConfigsForRegistry` returns all configs; missing entries will break `createDefault()` .
- Ensure extension normalization matches callers' expectations (e.g., `.ts` vs `ts`).
- Test `getForFile` with edge cases: files without extensions, mixed-case names, Docker-compose style names.
- Confirm that the registry is imported and used where needed; otherwise legacy lookup paths may remain.