

packages/graph-core/src/languages/merge-configs.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:42:34.963Z

Overview

A new file `packages/graph-core/src/languages/merge-configs.ts` adds two exported helpers that merge hand-authored language configs with the automatically generated alphabetical catalog.

Key changes

- **Imports added** (R1-R2): `LanguageConfig` type and `buildAlphabeticalLanguageConfigs` builder.
- **`mergeLanguageConfigs`** (R8-R19):
 - Builds a `Map<string, LanguageConfig>` from `buildAlphabeticalLanguageConfigs()` (R10-R12).
 - Overwrites entries with the detailed array (R13-R15).
 - Returns the values sorted by `displayName` using `localeCompare` with `"en"` and base sensitivity (R16-R18).
- **`LanguageConfigsForRegistry`** (R22-R27):
 - Calls `mergeLanguageConfigs` (R24).
 - Separates catalog-only entries from detailed ones (R25-R26).
 - Returns `[...catalogOnly, ...detailed]` to preserve registration order (R27).

Both functions are exported (R8, R22).

Impact

- **Correctness:** Detailed configs override catalog entries on ID collision and the final list is alphabetically sorted by `displayName`.
- **Maintainability:** Centralizes merging logic; future changes to catalog generation or merging rules can be made in one place.
- **Performance:** Uses a single `Map` traversal and a final sort, yielding $O(n \log n)$ complexity.

Risks & follow-ups

- **Ordering:** `localeCompare` with `"en"` base sensitivity may produce unexpected order for names with diacritics.
- **Duplicate IDs:** If the catalog builder emits duplicate IDs, they could be silently overridden by detailed configs.
- **Test coverage:** Add unit tests for overlapping IDs, empty detailed lists, and large catalogs.
- **Build integration:** Verify that the new file is included in the TypeScript compilation and that its imports resolve in all target environments.