

packages/graph-core/src/persistence/persistence.test.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:45:30.195Z

Overview

A new test file `packages/graph-core/src/persistence/persistence.test.ts` (lines 1-204) was added to exercise the persistence API of the graph core module.

Key changes

- **Imports added** (lines 1-6): Vitest helpers (`describe` , `it` , `expect` , `beforeEach` , `afterEach`) and Node utilities (`mkdtempSync` , `rmSync` , `existsSync` , `writeFileSync` , `join` , `tmpdir`).
- **API coverage**: Tests for `saveGraph` / `loadGraph` , `saveMeta` / `loadMeta` , `saveFingerprints` / `loadFingerprints` , and `saveConfig` / `loadConfig` .
- **Edge-case checks**:
 - Verify that files are written under `.<tempDir>/.novadiff-graph/` .
 - Round-trip equality of graph, meta, fingerprints, and config objects.
 - `null` is returned when the expected file is missing.
 - `loadGraph` throws on a fatally invalid graph and respects a `{ validate: false }` option.
 - Corrupted JSON files result in `null` for fingerprints and config.
- **Default config**: `loadConfig` falls back to `{ autoUpdate: false, outputLanguage: "en" }` when `config.json` is absent or corrupted.

Impact

- Provides automated regression checks for persistence logic, catching serialization/deserialization bugs.
- Centralizes tests for future API changes.
- Exposes failures early by asserting file existence and content equality.

Risks & follow-ups

- Temporary directory creation (`mkdtempSync`) may fail on CI environments lacking write permissions; verify `/tmp` access.
- Tests assume the storage path `.novadiff-graph` ; any refactor of this path will break the suite.
- Default config values are hard-coded; changes to defaults will cause test failures.
- Only `loadGraph` currently accepts a `{ validate: false }` flag; ensure other loaders honor similar options if added.