

packages/graph-core/src/plugins/discovery.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:36:15.418Z

Overview

A new file `packages/graph-core/src/plugins/discovery.ts` introduces a lightweight plugin configuration system. It exports `PluginEntry`, `PluginConfig`, a default configuration, and helper functions for parsing and serializing JSON configs.

Key changes

- `import { builtinLanguageConfigs } (R1)` pulls language metadata for default plugin generation.
- `export interface PluginEntry (R3-R7)` defines a plugin entry with `name`, `enabled`, `languages`, and optional `options`.
- `export interface PluginConfig (R10-R12)` aggregates an array of `PluginEntry`.
- `DEFAULT_PLUGIN_CONFIG (R14-R24)` pre-populates a `tree-sitter` plugin with all languages that support Tree-Sitter, derived from `builtinLanguageConfigs`.
- `parsePluginConfig(jsonString) (R30-R60)` parses a JSON string, validates that `plugins` is an array and each entry has a non-empty `name`, a non-empty `languages` array, and an optional boolean `enabled`. On any failure it returns a shallow copy of `DEFAULT_PLUGIN_CONFIG`.
- `serializePluginConfig(config) (R66-R68)` returns a pretty-printed JSON string of the config.

Impact

- Provides a single source of truth for plugin config shape.
- Centralizes default config and parsing logic, reducing duplication.
- Existing code that imports `PluginConfig` can use the new module without breaking other modules.

Risks & follow-ups

- `parsePluginConfig` swallows all parse errors and silently falls back to defaults; callers should detect this case or add logging.
- `options` is optional and only type-checked; stricter validation may be needed if required.
- Default config construction filters and maps `builtinLanguageConfigs` on each import; monitor performance if the language set grows.
- Ensure any module that consumes `PluginConfig` imports this file and updates type references accordingly.