

packages/graph-view/src/App.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:33:07.407Z

Overview

`packages/graph-view/src/App.tsx` is a new root component that orchestrates token handling, demo mode, data fetching, and the dashboard UI. It imports React hooks, validation utilities, and the dashboard store, and lazy-loads heavy components.

Key changes

- **Imports** (R1-R6): added React hooks, `validateGraph` and `GraphIssue` from `@novadiff/graph-core/schema`, `useDashboardStore`, and core view components (`GraphView`, `DomainGraphView`, etc.).
- **Lazy loading** (R28-R34): `CodeViewer`, `LearnPanel`, `PathFinderModal`, and `KeyboardShortcutsHelp` are loaded with `React.lazy`.
- **Demo mode** (R36): `DEMO_MODE` flag controls URL resolution.
- **URL resolution** (R41-R55): `dataUrl` returns env-var URLs in demo mode or token-appended paths otherwise.
- **Token logic** (R61-R76): `resolveInitialToken` reads `token` from the query string or `sessionStorage`, clears the param, and persists the token.
- **App component** (R78-R97): shows `TokenGate` until a token is available; in demo mode it bypasses the gate.
- **Dashboard** (R99-R210): fetches `meta.json`, `config.json`, `knowledge-graph.json`, `diff-overlay.json`, and `domain-graph.json`; validates graphs with `validateGraph`; updates store view mode and error state.
- **DashboardContent** (R211-R709): consumes store state, registers keyboard shortcuts via `useKeyboardShortcuts` (disabled in embed mode), renders header, sidebar, and graph views, and conditionally shows overlays.
- **Export** (R709): `export default App;`

Impact

- Centralized data fetching simplifies future updates but ties the component to `@novadiff/graph-core`.
- Multiple fetches on mount may increase network traffic; lazy loading reduces initial bundle size.
- Error handling surfaces load and validation issues through banners.

Risks & follow-ups

- `DEMO_MODE` must be correctly set in CI; otherwise URLs resolve incorrectly.
- `resolveInitialToken` clears the URL query param; verify it does not leave stale tokens.

- Lazy-loaded chunks (`CodeViewer` , `LearnPanel` , etc.) must be present in production builds; missing files could break the UI.