

packages/graph-view/src/components/CodeViewer.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:17:02.413Z

Overview

A new `CodeViewer.tsx` component is added at `packages/graph-view/src/components`. It renders source files from the dashboard graph, supports line selection, and can request code explanations via the NovaDiff embed API.

Key changes

- **Imports** – React hooks, `createPortal`, Prism-renderer (`Highlight`, `themes.vsDark`), and context hooks (`useDashboardStore`, `useI18n`, `useNovaDiffEmbed`).
- **Interfaces** – `SourceFile` (path, language, content, sizeBytes, lineCount) and `CodeViewerProps` (accessToken, presentation, onClose, onExpand).
- **Utility functions** – `fileContentUrl`, `fallbackLanguage`, and `formatBytes`.
- **State** – `SourceState` tracks loading, loaded, and error states.
- **Data fetching** – Uses `fetch(fileContentUrl(...))` or `embed.readFile` when `accessToken === "__novadiff__"`.
- **Selection** – `selectAnchor`, `selectEnd`, `userSelection`, and `highlightedRange` manage line-range selection and node-range highlighting.
- **Explain code** – `runExplainCode` calls `embed.explainCode` and displays the result in a portal-rendered `ExplainCodeModal`.
- **UI** – Header shows file info, a Prism-highlighted code block with line numbers, and buttons for explain, expand, and close.

Impact

- **Correctness** – Explicit async handling for fetch and embed calls; error messages surface via `t.codeViewer.*` strings.
- **Maintainability** – Centralizes file-view logic; reusable utilities and interfaces.
- **Performance** – Prism rendering may be heavy for large files; selection state updates trigger re-renders.
- **Compatibility** – Requires `react-dom` and `prism-react-renderer`; missing dependencies will break the build.
- **Observability** – Uses `useI18n` for all UI text; errors are shown in the UI.

Risks & follow-ups

- **Dependency availability** – Verify that `react-dom` and `prism-react-renderer` are listed in the package's `package.json`.
- **Portal target** – `createPortal` renders into `document.body`; confirm this is acceptable for the host environment (e.g., SSR).
- **Selection logic** – Rapid clicks could produce inconsistent ranges; test shift-click behavior.

- **NovaDiff embed** – The component assumes `embed.readFile` and `embed.explainCode` exist; test with demo and production tokens.