

packages/graph-view/src/components/CustomNode.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:18:20.868Z

Overview

A new `CustomNode` component is added to `packages/graph-view/src/components/CustomNode.tsx`. It renders a custom node for XYFlow with color bars, handles, and diff/selection overlays.

Key changes

- **Imports** (lines 1-5): `memo` from `react`; `Handle`, `Position` from `@xyflow/react`; type imports for `NodeProps`, `Node`, `NodeType`; `useI18n` from context.
- **Color maps** (lines 8-30 and 32-54) keyed by `NodeType` to keep styling consistent with the core union.
- **Data contract** (`CustomNodeData`, lines 62-80) defines node metadata and UI flags.
- **Node type alias** (`CustomFlowNode`, line 82) registers the `"custom"` node with XYFlow.
- **Component logic** (`CustomNodeComponent`, lines 84-187) renders the card, applies classes based on flags, and uses `useI18n` for labels.
- **Memoization** (line 189) wraps the component with `memo` to avoid unnecessary re-renders.
- **Export** (line 190) exposes `CustomNode` as the default export.

Impact

- Provides type safety for node data via `CustomNodeData`.
- Emits a dev-time warning for unknown `nodeType` values (lines 94-96).
- Diff overlay classes (`diff-changed-glow`, `diff-affected-glow`) give visual cues for changes.
- Memoization improves rendering performance for unchanged nodes.

Risks & follow-ups

- Color maps must stay in sync with the core `NodeType` union; update after core changes.
- Unknown `nodeType` values trigger a warning; consider stricter validation or a fallback.
- i18n keys `t.customNode.tested` and `t.customNode.hasTests` must exist; run extraction to confirm.
- No unit tests exist for this component yet; add snapshot and interaction tests to guard against regressions.