

packages/graph-view/src/components/LearnPanel.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:27:19.116Z

Overview

`packages/graph-view/src/components/LearnPanel.tsx` (added lines R1-R230) introduces a new React component that renders a guided tour UI. It pulls tour data from the global dashboard store and uses the `i18n` context for all displayed strings.

Key changes

- **Imports** – added at the top of the file (lines 1-4):

```
``ts import { useMemo } from "react"; import ReactMarkdown from "react-markdown"; import { useDashboardStore } from "../store"; import { useI18n } from "../contexts/I18nContext";
```

```
- State extraction – selectors wired to the store (lines 7-16): `graph`, `tourActive`,  
`currentTourStep`, `startTour`, `stopTour`, `setTourStep`, `nextTourStep`, `prevTourStep`,  
`selectNode`, and the i18n hook `t`.  
- Tour logic – `useMemo` builds a sorted `tourSteps` array (lines 18-21). Conditional rendering  
handles three states:  
  1. No tour (`!hasTour`, lines 24-36).  
  2. Tour available but not started (`!tourActive`, lines 39-74).  
  3. Tour active (lines 77-229).  
- Markdown rendering – `ReactMarkdown` is configured with custom components for paragraphs,  
strong, code blocks, and lists (lines 121-154).  
- UI elements – progress bar, navigation dots, prev/next buttons, language lesson, and  
referenced component pills are rendered with Tailwind classes (lines 86-228).
```

Impact

- The component centralizes tour state in the dashboard store, keeping state logic in one place.
- `useMemo` limits recomputation of the sorted steps array.
- All UI strings are sourced from the `i18n` context, enabling localization.
- No existing modules are modified; the new file is isolated.

Risks & follow-ups

- **Store contract** – it is unknown from the diff whether the store actually contains the keys
(`graph.tour`, `tourActive`, etc.); missing keys could result in `undefined` values.
- **Markdown edge cases** – unknown from the diff whether `ReactMarkdown` will correctly render all
expected syntax; test with code blocks and nested lists.
- **Localization** – unknown from the diff whether all `t.learnPanel.\*` keys exist; missing
translations will show empty strings.
- **Accessibility** – unknown from the diff whether additional ARIA attributes are needed beyond
the existing `aria-label` on navigation dots.