

packages/graph-view/src/components/NodeInfo.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:30:08.762Z

Overview

A new component `NodeInfo` is added to `packages/graph-view/src/components/NodeInfo.tsx` (lines 259-538). It displays detailed information for a selected node, including domain-specific, knowledge-specific, and child relationships, and renders navigation history and badges.

Key changes

- **Imports** (lines 1-4): `useState`, `useDashboardStore`, `useI18n`, and type imports from `@novadiff/graph-core/types`.
- **Badge mappings** (lines 6-29, 31-35): `typeBadgeColors` and `complexityBadgeColors` map `NodeType` and complexity values to Tailwind classes, with fallbacks to the "file" badge.
- **Helper functions** (lines 37-45, 46-137, 138-257):
 - `getDirectionalLabel` (lines 37-45) localizes edge labels, falling back to a formatted string if `t.edgeLabels[edgeType]` is missing.
 - `KnowledgeNodeDetails` (lines 46-137) renders wikilinks, backlinks, and content previews for article/entity/topic/claim/source nodes.
 - `DomainNodeDetails` (lines 138-257) handles domain, flow, and step nodes, showing entities, rules, interactions, and flow steps.
- **Main component** (lines 259-538): uses `useState` for language expansion, pulls graph data via `useDashboardStore`, and renders navigation history, node badges, file info, tags, child nodes, and other connections.
- **Export** (line 259): `export default function NodeInfo()`.

Impact

- Provides a comprehensive node-detail panel, improving navigation and insight into graph structure.
- Centralizes node-specific rendering logic, reducing duplication.
- Multiple `useDashboardStore` hooks may trigger re-renders; selectors should be memoized.
- Requires the store to expose actions such as `navigateToDomain`, `selectNode`, `navigateToNode`, `goBackNode`, `setFocusNode`, and `openCodeViewer`.

Risks & follow-ups

- **Unknown node types:** line 315-317 warns if a node type is not in `typeBadgeColors`; ensure all `NodeType` values are covered.
- **Edge labeling:** line 40-42 falls back to a formatted string if `t.edgeLabels[edgeType]` is missing; verify translation files contain all edge types.

- **Store API changes:** the component relies on several store actions; any refactor of `useDashboardStore` could break navigation or focus logic.