

packages/graph-view/src/components/SearchBar.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T20:33:29.593Z

Overview

A new component `SearchBar.tsx` (lines 1-191) is added to `packages/graph-view/src/components`. It renders a text input that queries the dashboard store and shows a dropdown of the top five search results, with fuzzy/semantic mode toggles.

Key changes

- **Imports** – added React hooks (`useCallback` , `useEffect` , `useMemo` , `useRef` , `useState`) and store/context hooks (`useDashboardStore` , `useI18n`) R1-R3 .
- **Badge color map** – `typeBadgeColors` maps node types to Tailwind classes (file, function, class, ...) R5-R19 .
- **State & refs** – `dropdownOpen` , `containerRef` , `inputRef` control visibility and focus R34-R36 .
- **Node lookup** – `nodeMap` memoized from `graph?.nodes` R38-R42 .
- **Event handlers** – `handleInputChange` updates `searchQuery` and opens the dropdown; `handleResultClick` navigates to a node and closes the dropdown R46-R60 .
- **Effects** – two `useEffect` hooks close the dropdown on `Escape` key or outside clicks R62-R83 .
- **Render** – input with icon, mode buttons, result count, and a dropdown that lists each result with a type badge, name, relevance bar, and click handler R87-R190 .

Impact

- Adds a persistent search bar to the graph view, exposing store slices (`searchQuery` , `searchResults` , `graph` , `setSearchQuery` , `navigateToNodeInLayer` , `searchMode` , `setSearchMode`).
- Keeps rendering lightweight by limiting the dropdown to five items and memoizing the node map.
- Provides test hooks (`data-testid="search-input"`) and keyboard focus handling via refs.

Risks & follow-ups

- `nodeMap` relies on `graph?.nodes` ; if `graph` is undefined the map will be empty, potentially hiding results.
- The component depends on the exact shape of `useDashboardStore` ; any missing slice will cause runtime errors.
- Tailwind classes in `typeBadgeColors` must match the theme; mismatches could break styling.
- Verify that the global `keydown` and `mousedown` listeners correctly close the dropdown across browsers.