

packages/graph-view/src/contexts/I18nContext.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:46:15.076Z

Overview

New file `packages/graph-view/src/contexts/I18nContext.tsx` adds a lightweight i18n context for the graph-view package.

Key changes

- Imports: `createContext`, `useContext`, `useMemo`, `ReactNode` from `react` (line1) and `getLocale`, `resolveLocaleKey`, `Locale`, `LocaleKey` from `../locales` (line2).
- `interface I18nContextValue` (lines4-7) defines `locale`, `localeKey`, and `t`.
- `I18nContext` created with `createContext<I18nContextValue | null>(null)` (line10).
- `useI18n` hook (lines12-18) throws if the provider is missing.
- `I18nProvider` component (lines20-44) accepts optional `language` and `children`.
- Inside the provider: `localeKey` memoized via `resolveLocaleKey(language)` (line27); `locale` memoized via `getLocale(localeKey)` (line28).
- Provider value: `{ locale, localeKey, t: locale }` (lines32-34).

Impact

- The hook guarantees a context value, throwing when used outside `I18nProvider`.
- Locale logic is centralized, reducing duplication.
- Memoization limits recomputation when `language` or `locale` does not change.
- Components must be wrapped in `I18nProvider` to access `useI18n`.

Risks & follow-ups

- Verify all consumers of `useI18n` are inside an `I18nProvider`; otherwise an error will surface.
- Ensure `getLocale` and `resolveLocaleKey` return consistent results for the optional `language` prop; mismatches could break translation lookup.
- Test that the `t` field (currently set to `locale`) behaves as intended in downstream components.
- Confirm that the new context does not cause unnecessary re-renders when `children` change but locale remains the same.