

packages/graph-view/src/contexts/NovaDiffEmbedContext.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:46:51.133Z

Overview

A new context module `packages/graph-view/src/contexts/NovaDiffEmbedContext.tsx` is added to expose typed APIs for NovaDiff embeds.

Key changes

- **Imports** – `createContext`, `useContext` from React added at line 1 (R1).
- **Interfaces** –
 - `NovaDiffSourceFile` (R3-9) defines `path`, `language`, `content`, `sizeBytes`, `lineCount`.
 - `ExplainCodeRequest` (R11-17) specifies `filePath`, `startLine`, `endLine`, `snippet`, optional `symbolName`.
 - `NovaDiffEmbedContextValue` (R19-27) declares optional `readFile`, `embedMode`, and `explainCode`.
- **Context** – `NovaDiffEmbedContext` created with an empty default at line 30 (R30).
- **Hook** – `useNovaDiffEmbed` returns the context value (R32-34).

Impact

- Provides a typed contract for embed consumers, improving compile-time safety.
- Introduces a new public API `useNovaDiffEmbed`; components must use this hook to access the context.
- The default context is empty; consumers must guard against `undefined` properties, and missing providers can cause runtime errors.

Risks & follow-ups

- **Provider coverage** – ensure all embed consumers are wrapped by a provider that supplies `readFile` and `explainCode`; otherwise the functions will be `undefined`.
- **Runtime safety** – consider defensive checks or default no-op implementations to avoid crashes.
- **Linting** – run `npm run lint` to catch unused imports or type errors.
- **Compatibility** – update any stale imports of `NovaDiffEmbedContext` to use the new hook or context.