

packages/graph-view/src/hooks/useIsMobile.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:47:26.669Z

Overview

A new hook `useIsMobile` is added at `packages/graph-view/src/hooks/useIsMobile.ts`. It returns a boolean indicating whether the viewport width is below a configurable breakpoint (default `768 px`).

Key changes

- Import `useEffect` and `useState` from `react` (line 1).
- Define `DEFAULT_BREAKPOINT = 768` (line 3).
- Exported function `useIsMobile(breakpoint = DEFAULT_BREAKPOINT): boolean` (line 5).
- Media query string: `(max-width: ${breakpoint - 1}px)` (line 6).
- Initial state lazily computed: returns `false` when `typeof window === "undefined"` (SSR) and otherwise `window.matchMedia(query).matches` (lines 7-9).
- `useEffect` attaches a `change` listener to update state and cleans up on unmount (lines 12-18).
- Hook returns the current `isMobile` flag (line 20).

Impact

- Centralizes breakpoint logic; components can import a single hook instead of duplicating media-query code.
- SSR-safe: returns `false` on server, preventing hydration mismatches.
- Minimal overhead: one `matchMedia` listener per component instance.

Risks & follow-ups

- **SSR usage:** Components should not depend on the hook's value during the initial server render.
- **Listener cleanup:** Verify `removeEventListener` is called correctly; run unit tests for unmount scenarios.
- **Custom breakpoint:** Ensure passing a different breakpoint updates the query and listener.
- **Browser support:** `addEventListener` on `MediaQueryList` may not exist in older browsers; consider a polyfill if needed.