

packages/graph-view/src/hooks/useKeyboardShortcuts.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:48:02.102Z

Overview

A new file **packages/graph-view/src/hooks/useKeyboardShortcuts.ts** introduces a keyboard-shortcut system for the graph view.

- **Interface** `KeyboardShortcut` (lines 3-12) defines optional modifier flags (`ctrlKey` , `shiftKey` , `altKey` , `metaKey`) and required fields (`key` , `description` , `action` , `category`).
- **Hook** `useKeyboardShortcuts` (lines 14-51) registers a global `keydown` listener via `useEffect` (R1).
- **Formatter** `formatShortcutKey` (lines 52-71) builds a human-readable shortcut string.

Key changes

- **Interface:** added optional modifier flags and required fields (diff lines R3-R11).
- **Hook:**
 - Uses `useEffect` to attach a listener (R1).
 - Skips shortcuts when the event target is an `<input>` , `<textarea>` , or content-editable element unless the key is `Escape` (lines 21-27).
 - Matches shortcuts by key and modifier state, with a "not pressed" fallback (lines 29-34).
 - Prevents default for shortcuts involving `Ctrl` , `Meta` , or `Alt` (lines 37-40).
 - Executes `shortcut.action()` and breaks the loop (lines 41-42).
 - Cleans up by removing the listener (lines 47-48).
- **Formatter:**
 - Detects macOS via `navigator.userAgentData` or `navigator.platform` (lines 55-58).
 - Omits the Shift symbol for punctuation that inherently requires it (lines 63-65).
 - Returns the joined string (lines 70-71).

Impact

- **Correctness:** listener now ignores typing contexts and respects modifier combinations, reducing accidental activation (inferred from logic).
- **Maintainability:** centralizes shortcut logic in a single file, simplifying future extensions.
- **Performance:** a single global listener per component mount; cleanup handled in the effect's return.
- **Observability:** `formatShortcutKey` provides consistent UI labels for shortcut lists.

Risks & follow-ups

- Verify that the `keydown` listener does not interfere with existing global shortcuts elsewhere in the app (unknown from diff).
- Ensure `navigator.userAgentData` fallback correctly detects macOS on all target browsers (unknown from diff).

- Test that the `Escape` key still functions in input fields when shortcuts are disabled (unknown from diff).
- Confirm that the new interface does not break existing consumers that may have relied on implicit modifier defaults (unknown from diff).