

packages/graph-view/src/themes/ThemeContext.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:48:36.147Z

Overview

`packages/graph-view/src/themes/ThemeContext.tsx` introduces a React context for theme state, a `ThemeProvider` component, and a `useTheme` hook. The file adds local-storage persistence, optional host scoping, and utilities for preset resolution.

Key changes

- **Imports** (R1-R13) bring `HeadingFont`, `PresetId`, `ThemeConfig`, `ThemePreset` from `./types.ts`, `DEFAULT_THEME_CONFIG` from the same file, `getPreset` from `./presets.ts`, and `applyTheme`, `clearTheme` from `./theme-engine.ts`.
- **Context API:** `ThemeContext` is created at R25 with `createContext<ThemeContextValue | null>(null)` and exported via `ThemeProvider`.
- **Persistence helpers:** `loadFromLocalStorage` (R27-40) reads a JSON string under key `"ua-theme"` (R15); `saveToLocalStorage` (R41-47) writes the same key.
- **Initial theme resolution:** `resolveInitialTheme` (R49-51) prefers local storage, then `metaTheme`, finally `DEFAULT_THEME_CONFIG`.
- **Provider logic** (`ThemeProvider` at R60-135):
 - State `config` initialized by `resolveInitialTheme`.
 - `useEffect` (R68-82) applies theme on mount and on config changes, optionally scoping to a host `<div>` when `scopeToHost` is true.
 - Second `useEffect` (R84-94) clears host theme on unmount if scoped.
 - Third `useEffect` (R96-101) updates config when an async `metaTheme` arrives and no local preference exists.
 - `setPreset` (R103-108), `setAccent` (R110-112), and `setHeadingFont` (R114-116) update config via `useCallback`.
- **Hook** (`useTheme` at R136-140) consumes `ThemeContext` and throws if used outside a provider.

Impact

- Centralizes theme logic and state, reducing duplication.
- Local-storage sync prevents stale themes across reloads.
- Host scoping (when `scopeToHost` is true) confines CSS changes to a wrapper `<div>`, avoiding global thrashing.
- Existing components that call `useTheme` continue to work; no API changes.

Risks & follow-ups

- `loadFromLocalStorage` silently swallows parse errors (R36-38); malformed data may be ignored.

- If `scopeToHost` is true but the host `<div>` is missing, theme application fails silently (R70-75).
- The third `useEffect` (R96-101) may override a user-selected preset if `metaTheme` arrives after a local change; verify ordering.
- `clearTheme` runs only on unmount when scoped (R88-92); confirm global themes persist correctly after provider removal.