

packages/graph-view/src/themes/theme-engine.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:50:06.718Z

Overview

A new `theme-engine.ts` file was added at `packages/graph-view/src/themes/`. It centralizes theme application and teardown logic for the graph-view component.

Key changes

- **Imports** (lines 1-2): `ThemeConfig` type and `getAccent`, `getPreset` helpers.
- **hexToRgb** (lines 4-8): converts a hex string to an "R, G, B" string used for RGBA values.
- **deriveFromAccent** (lines 10-30): builds a set of derived CSS variables (e.g., `color-border-subtle`, `glass-bg`) based on an accent color and a dark-mode flag.
- **applyTheme** (lines 34-69):
 - Applies preset colors (`--color-...`).
 - Sets accent variables (`--color-accent`, `--color-accent-dim`, `--color-accent-bright`).
 - Adds derived variables via `deriveFromAccent`.
 - Sets `data-theme` attribute and heading-font CSS variable.
- **clearTheme** (lines 72-90): removes all theme-related inline styles and the `data-theme` attribute, enabling clean teardown.

Impact

- **Consistency:** All theme logic lives in one module, ensuring uniform CSS variable names and values across themes.
- **Performance:** Only a handful of `style.setProperty` / `removeProperty` calls per theme; negligible runtime cost.
- **Compatibility:** Uses standard CSS custom properties; no browser-specific code.

Risks & follow-ups

- `hexToRgb` has no validation; test with malformed hex strings to avoid runtime errors.
- `applyTheme` defaults to "serif" when `config.headingFont` is missing; confirm this matches design expectations.
- `clearTheme` must remove every property added by `applyTheme`; run integration tests after theme switches.
- Verify that `getPreset` and `getAccent` return the expected objects against existing preset data.