

packages/graph-view/vite.config.demo.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:20:08.337Z

Overview

A new Vite config file `packages/graph-view/vite.config.demo.ts` (lines R1-49) is added to bootstrap the demo build. It sets a base path, resolves core modules, injects a demo-mode flag, and configures chunk splitting and plugins.

Key changes

- **Imports** (R1-R4): ```ts import { defineConfig } from "vite"; import react from "@vitejs/plugin-react"; import tailwindcss from "@tailwindcss/vite"; import path from "path";`
- ```- **Export** (R6): export default defineConfig({ ... }) with base: "/demo/" (R7).`
- **Module resolution** (R9-R15): `resolve.alias` maps
 - `@novadiff/graph-core/schema` → `../core/dist/schema.js`,
 - `@novadiff/graph-core/search` → `../core/dist/search.js`,
 - `@novadiff/graph-core/types` → `../core/dist/types.js`.
- **Environment flag** (R17-R19): `define: { "import.meta.env.VITE_DEMO_MODE": JSON.stringify("true") }`.
- **Chunking** (R21-R44): `build.rollupOptions.output.manualChunks` splits React, XYFlow, graph-layout, and markdown-related dependencies into separate vendor bundles.
- **Plugins** (R48): `plugins: [react(), tailwindcss()]`.

Impact

- Core modules are resolved to the compiled `dist/*.js` files, enabling the demo to import them directly.
- The `VITE_DEMO_MODE` flag is available in `import.meta.env`, allowing demo-specific code paths.
- Manual chunking creates distinct vendor bundles for React, XYFlow, graph-layout, and markdown dependencies.

Risks & follow-ups

- The paths `../core/dist/*.js` must exist after the core build; missing files will break the demo.
- The regexes in `manualChunks` must match all intended modules; incorrect matches could leave dependencies in the main bundle.
- Run `vite build --config packages/graph-view/vite.config.demo.ts` to verify the base path and env flag.
- Ensure the `react` and `tailwindcss` plugins load without warnings on all target platforms.