

scripts/run-electron.cjs

Kind: modified · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:05:48.816Z

Overview

The launcher script `scripts/run-electron.cjs` now builds its environment by calling `augmentPathForCli` instead of a plain clone of `process.env`. The helper is imported from `electron/gh-path.cjs` (diff lines R18-R19). The removal of `ELECTRON_OVERRIDE_DIST_PATH` is unchanged.

Key changes

- In `cleanEnv` (lines 17-23) the original `const env = { ...process.env };` (L18) was replaced with: ````js const { augmentPathForCli } = require(path.join(root, "electron", "gh-path.cjs")); const env = augmentPathForCli({ ...process.env });`

- The ``delete env.ELECTRON_OVERRIDE_DIST_PATH;`` line remains at L20.
- No other parts of the script were modified.

Impact

- The environment passed to ``spawn`` now contains any modifications performed by ``augmentPathForCli``, which may adjust `PATH` or related variables.
- Existing behaviour that relied on a shallow clone of ``process.env`` is preserved except for the potential `PATH` changes.
- The change centralises path handling in ``gh-path.cjs``, reducing duplication.

Risks & follow-ups

- **Missing module**: ``electron/gh-path.cjs`` must exist and export ``augmentPathForCli``.
- **Path side-effects**: Verify that the augmented `PATH` does not interfere with other tooling.
- **Regression**: Ensure that deleting ``ELECTRON_OVERRIDE_DIST_PATH`` still behaves as intended after augmentation.
- **Documentation**: Update any references to the old ``process.env`` clone.