

src/app/launchSequence.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:04:12.736Z

Overview

`src/app/launchSequence.ts` is a new module that exports constants and helper functions for tracking whether the app's launch sequence has finished. The file adds lines 1-8 (constants), line 10 (type), lines 12-18 (`readLaunchSkipped`), and lines 20-26 (`markLaunchComplete`).

Key changes

- **Constants**

- `LAUNCH_SESSION_KEY = "novadiff-launch-done-v1"` (R1) – key used in `sessionStorage`.
- `LAUNCH_HOLD_MS = 2400` (R4) – minimum display time on the finished boot screen.
- `LAUNCH_HOLD_SKIP_AFTER_MS = 900` (R6) – earliest point the user may skip the hold.
- `LAUNCH_EXIT_FADE_MS = 580` (R7) – fade-out duration.
- `LAUNCH_REVEAL_MS = 1200` (R8) – reveal animation duration.

- **Type**

- `LaunchPhase = "boot" | "reveal" | "ready"` (R10).

- **Functions**

- `readLaunchSkipped()` (R12-R18) reads the flag from `sessionStorage`, returning `true` if the key equals `"1"`. Errors are caught and `false` is returned.
- `markLaunchComplete()` (R20-R26) writes `"1"` to `sessionStorage` under the key, with a silent catch for storage errors.

Impact

- Provides a single source of truth for launch completion that survives page reloads.
- Centralizes timing constants, simplifying future adjustments.
- Uses `sessionStorage`; if unavailable (e.g., in privacy-mode browsers), the try/catch prevents crashes but silently ignores failures.

Risks & follow-ups

- **Storage availability** – verify that `sessionStorage` is accessible in all target environments; consider a fallback if it is blocked.
- **Silent error handling** – the catch blocks swallow errors; adding diagnostics could surface hidden issues.
- **Dead code** – the module's exports are not referenced elsewhere in the diff; ensure they are imported where needed.
- **Testing** – no unit tests cover this module; tests should confirm flag persistence and error handling.