

src/app/usePrefersReducedMotion.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:05:20.653Z

Overview

A new hook, `usePrefersReducedMotion`, is added to `src/app/usePrefersReducedMotion.ts` (lines 1-19). It exposes the user's reduced-motion preference in a type-safe, SSR-friendly way.

Key changes

- **Imports** `useEffect` and `useState` from `react` (line 1).
- **Exports** `function usePrefersReducedMotion(): boolean` (line 3).
- **State initialization** uses `useState(() => { ... })` (lines 4-8), guarding against `window` being undefined and falling back to `false`.
- **Media query** `window.matchMedia("(prefers-reduced-motion: reduce)")` determines the initial value.
- **Effect** sets up a `change` event listener on the media query (lines 11-15) and cleans it up on unmount.
- **Return** the current `reduced` boolean (line 18).

Impact

- Provides a reusable, lightweight hook for accessibility-aware components.
- Adds negligible runtime overhead; the listener is added once per component instance.
- SSR safe: defaults to `false` when `window` is undefined, preventing hydration mismatches.
- No new external dependencies; relies on native `matchMedia`.

Risks & follow-ups

- Verify that components using this hook render consistently on server and client to avoid hydration warnings.
- Test in browsers lacking `matchMedia` (e.g., IE11) to confirm the fallback to `false` behaves correctly.
- Ensure the `change` listener cleanup runs properly to avoid memory leaks in long-lived components.
- Add unit tests covering initial state, listener updates, and the SSR guard.