

src/components/PullRequestsWorkspace.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:15:35.966Z

Overview

A new `PullRequestsWorkspace` component is added at `src/components/PullRequestsWorkspace.tsx` (lines 28-324).

It provides a UI for browsing GitHub repositories, discovering local clones, and launching pull-request comparisons in the NovaDiff desktop app.

Key changes

- **Imports** (lines 1-10): React hooks, Lucide icons, and types from `../app/gitTypes` (`GithubPullRequestSummary`, `GithubRepoSummary`, `GitToolingStatus`, `LocalRepoMatch`).
- **Props interface** (lines 17-26): `PullRequestsWorkspaceProps` defines `onOpenCompare` and `onUseRepoAsTarget` callbacks.
- **State** (lines 33-42): `tooling`, `repos`, `selectedRepo`, `localMatches`, `prs`, `loading`, `prsLoading`, `error`, `repoFilter`, `busyPr`.
- **API calls** (lines 46-68, 74-87, 89-113, 115-142): use `window.electronAPI` methods `gitDetectTooling`, `githubListRepos`, `gitMatchLocalRepo`, `githubListPrs`, `githubPrCompareRoots`.
- **UI** (lines 153-324): header with refresh button, status cards, login prompt, repo list with search, PR list with compare buttons, and local-clone actions.
- **Error handling**: descriptive messages set when API calls fail or prerequisites are missing.

Impact

- **Runtime dependency**: the component requires all referenced `electronAPI` methods; missing ones will cause runtime errors.
- **Large lists**: the component renders full repo and PR arrays (`filteredRepos.map`, `prs.map`) without virtualization, which could affect responsiveness for many items.
- **State updates**: no cancellation logic for pending promises; long-running API calls may update state after the component unmounts.

Risks & follow-ups

- **API contract**: verify that `window.electronAPI` exposes `gitDetectTooling`, `githubListRepos`, `gitMatchLocalRepo`, `githubListPrs`, and `githubPrCompareRoots`.
- **Promise cleanup**: consider adding abort logic to prevent state updates on unmounted components.
- **Layout fit**: the component uses flexbox panels; test on various screen sizes to ensure content remains visible.
- **Testing**: add unit tests for the callbacks and integration tests for the full workflow.