

src/components/launch/AppLaunchShell.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:29:49.178Z

Overview

A new component `src/components/launch/AppLaunchShell.tsx` (lines 1-76) is added. It implements a launch sequence state machine, reduced-motion handling, and exposes a context for downstream components.

Key changes

- **Exports**
 - `AppLaunchShellProps` (optional `chrome`, required `children`, optional `onPhaseChange`) – added at lines 13-18.
 - `AppLaunchShell` function – added at line 19.
- **Imports** – added at lines 1-11:
 - React hooks (`useCallback`, `useEffect`, `useMemo`, `useState`).
 - `LAUNCH_REVEAL_MS`, `LaunchPhase`, `markLaunchComplete`, `readLaunchSkipped` from `../../app/launchSequence`.
 - `usePrefersReducedMotion` from `../../app/usePrefersReducedMotion`.
 - `LaunchProvider` from `./LaunchContext`.
 - `LaunchBoot` from `./LaunchBoot`.
 - CSS from `./launch.css`.
- **State logic** –
 - `skipSequence` is `true` when reduced motion is preferred or `readLaunchSkipped()` returns true.
 - Initial `phase` is `"ready"` if skipping, otherwise `"boot"`.
 - `bootVisible` tracks whether the boot UI should be shown.
- **Callbacks & effects** –
 - `onBootExitComplete` sets `bootVisible` to false, moves to `"reveal"`, and calls `markLaunchComplete()`.
 - An effect transitions from `"reveal"` to `"ready"` after `LAUNCH_REVEAL_MS`.
 - Another effect calls `onPhaseChange` whenever `phase` changes.
- **Context** – `LaunchProvider` supplies `{ phase, skipSequence, brandReveal }` where `brandReveal` is true for `"reveal"` or `"ready"`.
- **Rendering** – Conditionally shows `LaunchBoot`, an optional chrome panel with motion classes, and the children wrapped in a shell div.

Impact

- Adds a launch flow that can skip the boot sequence when reduced motion is enabled or previously skipped.
- Downstream consumers receive `skipSequence` and `brandReveal` in addition to `phase`.
- New CSS classes (`is-launched`, `is-revealing`, `is-ready`) drive visual transitions.

- `markLaunchComplete()` is invoked after boot exit, setting the launch completion flag.

Risks & follow-ups

- Verify that `LAUNCH_REVEAL_MS`, `LaunchPhase`, `markLaunchComplete`, and `readLaunchSkipped` are exported from `launchSequence`.
- Ensure `LaunchBoot` accepts an `onExitComplete` prop; otherwise a runtime error will occur.
- Test that `skipSequence` correctly bypasses the boot UI and sets the phase to `"ready"`.
- Confirm that existing `LaunchContext` consumers handle the new `brandReveal` flag without breaking.
- Run the repo's lint, test, and production build scripts to catch any type or runtime issues.