

src/components/launch/LaunchContext.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:30:50.285Z

Overview

A new `LaunchContext` module was added to `src/components/launch`. It introduces a typed React context for the launch sequence, a provider component, and a custom hook for consumption.

Key changes

- **Imports** (R1-R2): `createContext`, `useContext` from React and `LaunchPhase` type from `../../app/launchSequence`.
- **LaunchContextValue interface** (R4-R7): defines `phase: LaunchPhase`, `skipSequence: boolean`, `brandReveal: boolean`.
- **Context creation** (R10-R14): default values `phase: "ready"`, `skipSequence: true`, `brandReveal: true`.
- **LaunchProvider component** (R16-R24): accepts `value` and `children`, renders `<LaunchContext.Provider>`.
- **useLaunch hook** (R26-R28): returns `useContext(LaunchContext)`.

Impact

- **Type safety:** The interface enforces a consistent shape for launch data, catching mismatches at compile time.
- **Centralized state:** Components can share launch information through a single context, reducing duplicated logic.
- **Observability:** Default values give a clear starting state for debugging and testing.

Risks & follow-ups

- **Provider omission:** Verify that all consumers of `useLaunch` are wrapped in `LaunchProvider`.
- **Default value assumptions:** Ensure that the defaults (`"ready"`, `true`, `true`) match the intended UI state.
- **Type mismatches:** Run TypeScript linting to confirm that `LaunchPhase` values used elsewhere align with the interface.
- **Testing coverage:** Add unit tests for `LaunchProvider` and `useLaunch` to guard against regressions.