

src/components/launch/TypewriterText.tsx

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T19:31:34.638Z

Overview

A new component, `TypewriterText`, is added at `src/components/launch/TypewriterText.tsx`. It renders a typewriter-style animation with an optional cursor, reduced-motion support, and a completion callback.

Key changes

- **Imports:** `useEffect`, `useRef`, `useState` from `React` (lines 1-2) and `usePrefersReducedMotion` from `../../app/usePrefersReducedMotion` (line 2).
- **Props interface** (`TypewriterTextProps`, lines 4-15): `text`, optional `active`, `persist`, `speed`, `delay`, `className`, `showCursor`, and `onComplete`.
- **Component** (`export function TypewriterText`, lines 17-99): sets defaults, tracks `visible` state, and uses refs for `onComplete`, completion status, and active state.
- **Reduced-motion handling** (lines 52-56): if `reduced` is true, the full text is shown immediately and `onComplete` is called.
- **Typing logic** (lines 59-79): a `setTimeout` for `delay` starts a `setInterval` that increments `visible` by `speed` until the full text is displayed, then clears timers and triggers `onComplete`.
- **Cleanup** (lines 81-86): cancels timers and resets `wasActiveRef`.
- **Render** (lines 91-97): displays the current slice of text and, if `showCursor`, `active`, and not finished or reduced, shows a cursor element.

Impact

- Introduces a reusable UI element; no existing API changes.
- Adds a dependency on `usePrefersReducedMotion`; the hook must be exported and functional.
- Adds hooks and timers; the performance impact is expected to be minimal.
- Other components remain unaffected and can import `TypewriterText` directly.

Risks & follow-ups

- **Reduced-motion detection:** verify that `usePrefersReducedMotion` correctly reads the user preference; otherwise the animation may always run.
- **Callback firing:** confirm `onComplete` is invoked exactly once per full run; the ref logic should prevent duplicate calls.
- **Active toggling:** when `active` becomes false, the component resets unless `persist` is true and the text has already completed.
- **Cursor logic:** ensure cursor visibility respects `showCursor`, `active`, `reduced`, and completion state.