

electron/gh-path.cjs · Code explanation (L63-90)

Kind: modified · Baseline: 984f0748954a · Target: NovaDiff · Requested mode: exact · Effective mode: exact ·
Generated: 2026-05-27T05:41:35.662Z

What it does `resolveViaLoginShell` attempts to locate the `gh` executable by invoking a login shell and asking it to resolve the command path. It returns the absolute path to `gh` if found, or `null` if it cannot determine the location or if the platform is Windows.

How it works
1. Platform guard – If `process.platform === "win32"`, the function immediately returns `null` because the login-shell strategy is not applicable on Windows.
2. *Shell candidates

- It defines an array `shells` containing two tuples: `["/bin/zsh", ["-ilc", "command -v gh"]]` and `["/bin/bash", ["-lc", "command -v gh"]]`.
*3. *Iterate over shells*
- For each `[shell, args]` pair:
- Skip the shell if `fssync.existsSync(shell)` is `false`.
- Run the shell with `spawnSync`, passing `args`, `env`, `encoding: "utf8"`, and a `timeout` of `8000ms`.
- Capture the first line of `stdout`, trim it, and store it in `found`.
- If `found` is non-empty and `fssync.existsSync(found)` is `true`, return `found`.
*4. *Fallback*
- If none of the shells yield a valid path, the function returns `null`.

Notes for reviewers– The function relies on `spawnSync`'s synchronous behavior; any error during execution is silently ignored (`catch {}`), so the next shell is tried.– The timeout of `8000ms` may be too short for very slow shells; consider making it configurable.– The function only checks `/bin/zsh` and `/bin/bash`; other shells (e.g., `fish`, `tcsh`) are not considered.– The returned path is verified with `fssync.existsSync`, ensuring the file actually exists before returning it.