

electron/llm.cjs · Code explanation (L1162-1175)

Kind: modified · Baseline: 984f0748954a · Target: NovaDiff · Requested mode: exact · Effective mode: exact ·
Generated: 2026-05-27T06:07:07.083Z

What it does `probeProvider` is an async helper that sends a minimal prompt to a language-model provider and returns a short response. It always resolves with an object `{ ok: true, reply: ... }`, where `reply` is the first200 characters of whatever the provider returned.

How it works

1. It builds a hard-coded prompt that instructs the model to reply with only the word `ok`.
2. It calls `completeChat` (assumed to be an LLM wrapper) with the supplied `provider`, `baseUrl`, and `model`, passing the prompt and a 20s timeout.
3. After awaiting the completion, it slices the first200 characters of the returned string and packages it with `ok: true`.
4. No validation of the content or error handling is performed; the function always reports success.

Notes for reviewers- The function never checks whether the reply actually contains the expected word `ok`; it simply returns the raw output.- `ok: true` is hard-coded, so any provider failure (network error, timeout, or malformed response) will still be reported as success, potentially masking issues.- The `reply.slice(0,200)` truncation may cut off the entire response if it is shorter than 200 characters; consider returning the full reply or handling length explicitly.- `completeChat` is assumed to return a string; if it returns an object, `reply.slice` will throw. Clarify the return type of `completeChat`.- No retry logic is present; a single failure will propagate as a rejection of the promise.- The prompt is static; if the provider's behavior changes, the probe may become ineffective. Consider parameterizing the expected response.