

electron/main.cjs · Code explanation (L115-120)

Kind: modified · Baseline: 984f0748954a · Target: NovaDiff · Requested mode: exact · Effective mode: exact ·
Generated: 2026-05-27T06:24:48.674Z

What it does `getTargetWindow` determines the `BrowserWindow` instance that should receive an action. It accepts an `event` (typically an IPC event) and returns either the window that sent the event, the currently focused window, or falls back to a global `mainWindow` if neither is available.

How it works 1. **Check for a sender** – `if (event?.sender)` uses optional chaining to see if the event carries a `sender`. 2. ***Return the sender's window**

- – `BrowserWindow.fromWebContents(event.sender)` converts the `WebContents` of the sender into its owning `BrowserWindow`. 3. ***Fallback to mainWindow**
- – If the conversion yields `null` or `undefined`, the nullish coalescing operator (`??`) returns `mainWindow`. 4. ***No sender case**
- – If `event?.sender` is falsy, the function calls `BrowserWindow.getFocusedWindow()` to get the window currently in focus. 5. ***Final fallback**
- – Again, `?? mainWindow` ensures a window is always returned, even if no window is focused.

Notes for reviewers- `mainWindow` is referenced but not defined in the snippet; confirm it is a valid global `BrowserWindow` elsewhere. - The function guarantees a non-null return, which is useful for IPC handlers that need a target window. - Consider whether the fallback to `mainWindow` is appropriate in all contexts (e.g., when no window should be targeted). - Ensure that `BrowserWindow.fromWebContents` and `getFocusedWindow` are imported from `Electron`; otherwise the code will fail at runtime.