

electron/main.cjs · Code explanation (L598-614)

Kind: modified · Baseline: 984f0748954a · Target: NovaDiff · Requested mode: exact · Effective mode: exact ·
Generated: 2026-05-27T06:22:29.052Z

What it does `sendKnowledgeGraphProgress` forwards progress updates from the main process to a renderer window. It accepts an `event` (typically an IPC event) and a `payload`. If the payload is a string, it parses a "current/total" pattern and sends a structured message; otherwise it forwards the payload unchanged, defaulting to an empty message when `payload` is `null` or `undefined`.

How it works1. `const wc = event?.sender;` grabs the `webContents` that emitted the event.2. `if (!wc || wc.isDestroyed()) { return; }` exits early if the target window is missing or already closed.3. When `payload` is a string, it runs `payload.match(/(\d+)\s*\./s*(\d+)/)` to extract two numbers.4. It then calls `wc.send("knowledge-graph-progress", { ... })` with:

- `message` : the original string,
- `phase` : hard-coded "extract",
- `current` and `total` : parsed numbers or `undefined` if the regex fails.5. If `payload` is not a string, it sends it directly (or `{ message: "" }` if falsy) via the same channel.

Notes for reviewers

- The function assumes `event.sender` is a `webContents` instance; the snippet does not verify its type.
- The regex only captures digits; non-numeric progress strings will result in `current / total` being `undefined`.
- The hard-coded "extract" phase suggests this helper is tied to a specific workflow; consider parameterizing it if reuse is needed.
- No error handling is present for malformed payloads beyond the regex check.
- Unknown from the snippet: the broader context of how `sendKnowledgeGraphProgress` is invoked and what the renderer expects.