

packages/graph-core/src/plugins/extractors/ruby-extractor.ts · Code explanation (L70-84)

Kind: modified · Baseline: 984f0748954a · Target: NovaDiff · Requested mode: exact · Effective mode: exact ·
Generated: 2026-05-27T06:14:44.479Z

What it does `extractAttrProperties` takes a `TreeSitter` node that represents a method call and returns an array of attribute names that were passed as symbol arguments. For example, given a call node for `foo( :name, :age )`, it will return `[ "name", "age" ]`.

How it works 1. It initializes an empty array `properties`. 2. It retrieves the child node that holds the call's arguments via `callNode.childForFieldName("arguments")`. If this node is missing, it immediately returns the empty array. 3. It loops over each child of the arguments node (`args.childCount`). 4. For each child, it checks whether the node exists and its `type` equals `"simple_symbol"`. 5. When a simple symbol is found, it removes the leading colon by slicing the node's text (`child.text.slice(1)`) and pushes the resulting string into `properties`. 6. After iterating all children, it returns the populated `properties` array.

Notes for reviewers- The function has no side effects; it only reads from the provided `callNode`. - It assumes that `child.text` contains the raw source text of the symbol, which is typical for `TreeSitter` Ruby nodes. - The implementation ignores any arguments that are not simple symbols (e.g., literals, method calls). - If the arguments node is absent, the function correctly returns an empty array, which is useful for calls without symbol arguments. - Unknown from the snippet: the exact behavior of `childForFieldName`, `childCount`, and `child.text` depends on the `TreeSitter` Ruby grammar, but the code follows the standard API for accessing node children.