

cli/src/main.rs · Code explanation (L85-90)

Kind: modified · Baseline: 46a8da0664d1 · Target: NovaDiff · Requested mode: exact · Effective mode: exact ·
Generated: 2026-05-19T22:57:39.865Z

What it does `PrefetchSummaryJob` is a plain data holder used by the CLI to schedule a pre-fetch operation for a repository subtree.- `path` stores the filesystem path of the target subtree.- `kind` indicates the type of change (`ChangeKind`) that triggered the job.- `depth` records how deep the subtree is relative to the repository root, which can influence pre-fetch strategy.- `parent_subtree_weight` holds the cumulative weight of the parent subtree, likely used to prioritize or limit pre-fetching based on size.

How it worksWhen the CLI detects a change, it creates an instance of `PrefetchSummaryJob` with the relevant metadata. This struct is then passed to the pre-fetch worker queue. The worker reads the fields to determine which files to load into the cache, how aggressively to pre-fetch, and whether to skip or defer the job based on `parent_subtree_weight` . The struct itself contains no methods; it is purely a transport object.

Notes for reviewers- The struct is immutable; all fields are public, so callers can construct it directly.- `ChangeKind` is referenced but not defined here; ensure its enum variants match the expected change types.- `depth` and `parent_subtree_weight` are `usize` ; confirm that overflow is impossible in the expected use cases.- No validation logic is present; consider adding a constructor or `impl` block if invariants need enforcement.- The struct is lightweight and serializable, making it suitable for inter-thread communication.