

electron/preload.cjs

Kind: modified · Baseline: 46a8da0664d1 · Target: NovaDiff · Generated: 2026-05-19T22:36:27.031Z

Overview

Added two IPC-exposed functions to `electron/preload.cjs` at lines 136-141:

`workspaceRefreshHistory` and `workspaceUpdateUiState`. They forward a payload to the main process via `ipcRenderer.invoke` on the channels `"workspace-refresh-history"` and `"workspace-update-ui-state"`.

Key changes

- New API functions inserted at lines 136-141 (diff lines R136-R141).
- Each function simply calls `ipcRenderer.invoke` with the corresponding channel and payload.
- No other imports or logic were altered; the surrounding API surface remains unchanged.

Impact

- Adds renderer-side hooks for refreshing workspace history and updating UI state without affecting existing behavior.
- No breaking changes; existing code continues to work.
- The new functions follow the same pattern as other `workspace*` helpers, keeping the preload API consistent.

Risks & follow-ups

- **Missing main-process handlers:** Verify that `"workspace-refresh-history"` and `"workspace-update-ui-state"` are implemented in the main process; otherwise calls will fail.
- **Documentation:** Update API docs and README to expose the new functions.
- **Testing:** Add unit/integration tests to confirm the new IPC calls reach the main process and return expected results.