

packages/graph-view/src/hooks/useEmbedAutoExpand.ts

Kind: added · Baseline: 46a8da0664d1 · Target: NovaDiff · Generated: 2026-05-19T22:50:02.393Z

Overview

A new hook `useEmbedAutoExpand` is added under `packages/graph-view/src/hooks/`. It orchestrates automatic expansion of folder containers and viewport fitting when the NovaDiff embed is active and the graph layout is ready.

Key changes

- **Imports:** added `useEffect`, `useRef`, `useState` from `React`, `useReactFlow` from `@xyflow/react`, `useDashboardStore` from the store, and `useNovaDiffEmbed` from the embed context.
- **Constants:** `EXPAND_POLL_MS` (100 ms) and `EXPAND_TIMEOUT_MS` (120 000 ms) control the polling loop for layout readiness.
- **Interface:** `EmbedAutoExpandInput` defines the hook's contract (`navigationLevel`, `activeLayerId`, `layoutReady`, `containerIds`, `graphFingerprint`).
- **Helper functions:** `containersFullyLaidOut` checks if all target containers are expanded and cached; `waitForContainerLayouts` polls until layouts are ready or timeout.
- **Hook logic:**
 - Triggers only in embed mode and when `navigationLevel` is `"overview"` or `"layer-detail"`.
 - Expands missing containers via `expandManyContainers`.
 - After expansion, waits for layouts, then calls `fitView` with a smooth animation.
 - Manages an `isExpanding` state and a cancellation flag to avoid state updates after unmount.

Impact

- **Correctness:** Guarantees that the viewport is only fitted after all containers are fully laid out, preventing premature zooming.
- **Performance:** Introduces a polling loop (`EXPAND_POLL_MS`) that may add minor overhead; the timeout (`EXPAND_TIMEOUT_MS`) protects against infinite waits.
- **Maintainability:** Centralizes embed-specific expansion logic; future changes to container expansion or viewport fitting can be made in one place.
- **Observability:** Exposes `isExpanding` for UI feedback (e.g., loading spinners) and logs can be added around the polling for debugging.

Risks & follow-ups

- **Race conditions:** Verify that `expandManyContainers` completes before `waitForContainerLayouts` starts; the current implementation assumes immediate state updates.

- **Memory leaks:** Ensure the cleanup function correctly sets `cancelledRef.current` to avoid state updates after component unmount.
- **Compatibility:** Confirm that `useDashboardStore.getState().enterNovaDiffEmbedDepth()` and `expandedContainers` exist in all target environments.
- **Testing:** Add unit tests for the polling logic and the `fitView` call sequence to catch regressions when layout data changes.