

src/app/launchSequence.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:26:05.980Z

Overview

A new file `src/app/launchSequence.ts` (added) introduces launch-related constants, a `LaunchPhase` type, and two helper functions that persist launch state in `sessionStorage`.

Key changes

- **Exports** (R1-8, R10):
 - `LAUNCH_SESSION_KEY`, `LAUNCH_HOLD_MS`, `LAUNCH_HOLD_SKIP_AFTER_MS`, `LAUNCH_EXIT_FADE_MS`, `LAUNCH_REVEAL_MS` (lines R1-8).
 - `LaunchPhase` type (line R10).
 - `readLaunchSkipped()` and `markLaunchComplete()` (lines R12-26).
- **Behavior** (R12-26):
 - `readLaunchSkipped()` returns `true` when `sessionStorage.getItem(LAUNCH_SESSION_KEY) === "1"`, otherwise `false`.
 - `markLaunchComplete()` stores `"1"` under `LAUNCH_SESSION_KEY`.
 - Both functions wrap storage access in `try/catch` to avoid errors if `sessionStorage` is unavailable.

Impact

- Centralizes launch constants and state logic, simplifying future updates.
- Adds minimal runtime cost: only simple `sessionStorage` reads/writes.
- Functions are safe in environments without `sessionStorage` (e.g., SSR) due to error handling.

Risks & follow-ups

- Unknown from the available diff/scan evidence whether all target browsers expose `sessionStorage`; fallback behavior is acceptable.
- Verify that existing launch flow imports this module and uses the exported constants consistently.
- Run lint, test, and production build pipelines to confirm the new file compiles without errors.
- Update internal documentation to expose the new API.