

src/app/usePrefersReducedMotion.ts

Kind: added · Baseline: 8e0dc031dcfc · Target: NovaDiff · Generated: 2026-05-19T21:27:33.874Z

Overview

A new React hook `usePrefersReducedMotion` was added in `src/app/usePrefersReducedMotion.ts`. It returns a boolean indicating whether the user prefers reduced motion and updates reactively.

Key changes

- New file `src/app/usePrefersReducedMotion.ts` (lines 1-19 added).
- Imports `useEffect` and `useState` from React (R1).
- Exports `function usePrefersReducedMotion(): boolean` (R3).
- Initializes state with `useState(() => { ... })` (R4-8).
- SSR guard: `typeof window === "undefined" || !window.matchMedia` → `false` (R5-6).
- Initial value from `window.matchMedia("(prefers-reduced-motion: reduce)").matches` (R8).
- `useEffect` adds a "change" listener on `mq` and updates state via `setReduced(mq.matches)` (R11-15).
- Cleanup removes the listener on unmount (R15-16).
- Hook returns the `reduced` state (R18-19).

Impact

- Provides a reusable, SSR-safe hook for reduced-motion preference.
- Adds a single event listener per mount; cleanup is handled.

Risks & follow-ups

- Verify that the default `false` during SSR matches hydration expectations.
- Ensure `matchMedia` and "change" events are supported in target browsers; consider polyfills if needed.
- Confirm that `removeEventListener` is invoked correctly on unmount.