

Overview

The `WelcomeScreen` component now accepts an optional `cachedGitUser` prop.

- `WelcomeScreenProps` gains `cachedGitUser?: GitUserProfile | null` (see L6).
- The component signature changes to `WelcomeScreen({ cachedGitUser, onComplete, onLocalOnly })` (R11).
- The `refresh` callback now lists `cachedGitUser?.login` in its dependency array (R67).
- After fetching users, the logic first checks if `cachedGitUser` matches a detected account and selects it; otherwise it falls back to the first user (R56-R58).

Key changes

- **Prop addition** – `cachedGitUser` added to `WelcomeScreenProps` (L6).
- **Signature update** – component now receives `{ cachedGitUser, onComplete, onLocalOnly }` (R11).
- **Dependency update** – `refresh` depends on `cachedGitUser?.login` (R67).
- **Selection logic** – auto-select cached user if present (R56-R58).
- **UI changes** –
 - Removed the old "Continue as @login" button block (L363-L384).
 - New continue button text shows "Use a different account" when a cached user exists, otherwise "Continue with GitHub" (R397).
 - Button disabled state now uses `selected` instead of `cachedGitUser` (R388).

Impact

- **User experience** – Cached accounts are pre-selected, reducing friction.
- **API contract** – Callers must provide `cachedGitUser` or handle its absence; omitting it may lead to default `undefined` behavior.
- **UI clarity** – Button text and disabled state reflect the presence of a cached user.

Risks & follow-ups

1. **Missing prop** – Verify that all imports of `WelcomeScreen` supply `cachedGitUser`; otherwise the component defaults to `undefined`.
2. **Selection edge case** – Ensure that when `cachedGitUser` is not in the detected list, the fallback still selects the first user (R58).
3. **Dependency array** – Confirm that adding `cachedGitUser?.login` to `refresh`'s deps triggers a refresh when the cached user changes (R67).

4. **UI regression** – Run visual tests to validate the new button text and disabled state (R397 , R388).