

src/app/mermaidBoot.ts · function runMermaidNodes

Kind: added · Baseline: NovaDiff-main · Target: NovaDiff · Requested mode: expanded · Effective mode: expanded · Symbol: function runMermaidNodes · Generated: 2026-05-14T07:16:28.001Z

Overview

The selected region in this diff represents a new function called `runMermaidNodes`, which is responsible for running Mermaid diagrams on a set of HTML elements. This function is added to the NovaDiff repository, which is a fork of the main NovaDiff repository. The function is located in the `src/app/mermaidBoot.ts` file.

Selected change

The selected change is an addition of a new function called `runMermaidNodes`. This function takes an array of HTML elements as input and runs Mermaid diagrams on them using the `mermaid` library. The function is asynchronous and returns a promise that resolves when the diagrams have been rendered.

Semantic context

The new function is added within the `src/app/mermaidBoot.ts` file, which is part of the NovaDiff repository. The file contains code related to the initialization and rendering of Mermaid diagrams. The new function is likely added to improve the performance or functionality of the existing Mermaid rendering code.

Risks & follow-ups

The addition of this new function may introduce new risks or issues, such as compatibility problems with other parts of the codebase or potential security vulnerabilities. It is important to thoroughly test the new function and ensure that it works correctly in all scenarios. Additionally, it may be necessary to update any relevant documentation or testing suites to reflect the changes made in the new function.