

electron/code-city-model.cjs

Kind: modified · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:18:33.854Z

Overview

The `electron/code-city-model.cjs` module now imports Node's `path` module (added at line 3) and extends `buildSideNodes` to emit a synthetic file-level symbol when a file has no explicit symbols (added lines 113-131). This ensures every file appears in the CodeCity model.

Key changes

- `const path = require("path");` added at the top of the file.
- In `buildSideNodes`, after retrieving `symbolEntries`, a guard `if (symbolEntries.length === 0)` pushes a new symbol:
 - `id: `${rootSide}:${relPath}:file:${path.basename(relPath)}``
 - `name: path.basename(relPath)`
 - `kind: "file"`
 - `startLine: 1, endLine: lineCount` (where `lineCount` is `Math.max(1, Number(file?.line_count ?? 0))`)
 - `lineCount`, `changeState`, `dominantAuthor`, and `owners` are inherited from the file's blame data.
- The synthetic symbol is added only when no real symbols exist for the file.

Impact

- **Completeness:** Guarantees a node for every file, preventing missing entries in visualizations.
- **No API change:** The payload shape returned by `buildCodeCityModelPayload` remains the same.
- **Minimal runtime cost:** Uses only Node's core `path` module and a single `path.basename` call per file.

Risks & follow-ups

- **Duplicate symbols:** Verify that the synthetic symbol does not collide with an existing symbol when a file actually contains symbols.
- **Performance:** The added `path.basename` call is trivial, but benchmark on large outlines if needed.
- **Linting:** Run `npm run lint` to confirm the new import satisfies style rules.
- **Testing:** Add unit tests for `buildSideNodes` covering the empty-symbol case.