

electron/git-service.cjs

Kind: modified · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:18:52.565Z

Overview

The `electron/git-service.cjs` file was extended with new Git-output parsing helpers and tooling detection. The changes add several functions (see line ranges R237-248, R250-269, R271-311, R314-330, R332-335, R337-344) and expose them via `module.exports` (R346-365).

Key changes

- `splitGitFormatLine` (R237-248): splits a string by `\x1f`, tab, or `%x1f`, falling back to the raw line.
- `parseLogLines` (R250-269): uses `splitGitFormatLine` to turn `git log` output into `{hash, shortHash, subject, authoredAt}` objects.
- `listBranches` (R271-311): parses `git for-each-ref` output, populating `upstream`, `isCurrent`, and `isRemote` flags.
- `listCommitsForRef` (R314-330): returns commits reachable from a ref, leveraging `parseLogLines`.
- `resolveRefHash` (R332-335): thin wrapper around `git rev-parse`.
- `detectGitTooling` (R337-344): reports whether Git is available, its version, and any error.
- `module.exports` (R346-365) now includes the new helpers alongside existing ones.

Impact

- The new splitter centralizes line-splitting logic, reducing duplication.
- Branch and commit discovery now rely on a single, more robust parsing routine.
- `detectGitTooling` provides a single source of truth for Git presence, useful for diagnostics.

Risks & follow-ups

- **Branch listing regression:** verify that upstream names and remote flags match expectations on all supported Git versions.
- **Log parsing edge cases:** ensure commit messages containing `\x1f` or tabs are handled correctly; run tests against repositories with such messages.
- **Performance:** benchmark `listBranches` on large repositories to confirm no measurable slowdown.
- **Tooling detection:** confirm that `detectGitTooling` reports errors when Git is missing or misconfigured, and that callers handle the `gitError` field.