

packages/graph-view/src/store.ts

Kind: modified · Baseline: 9aadd5eb5604 · Target: NovaDiff · Generated: 2026-05-26T19:49:09.466Z

Overview

`packages/graph-view/src/store.ts` now tracks an embedded-graph filter that can be synced with Code City node selections. The store adds a new state field, an action to update it, and clears layout caches when the filter or active layer changes.

Key changes

- Added `embedCityFilterNodeIds: Set<string> | null` to `DashboardStore` (R160-163) and initialized it to `null` in the store (R378-405).
- Implemented `setEmbedCityFilterNodeIds(ids)` (R379-380) to update the filter set, skip redundant updates, and clear layout caches (`containerLayoutCache` , `containerSizeMemory` , `expandedContainers` , `pendingFocusContainer`).
- Introduced `layerResetIfChanged` helper (lines 285-303) that clears container caches when the active layer changes.
- Updated `resetEmbedOverlays` to set `embedCityFilterNodeIds` to `null` (R684).
- Adjusted `setGraph` and navigation actions to reset caches when the graph or view mode changes.

Impact

- External components can now sync Code City filter selections to the embedded graph via `setEmbedCityFilterNodeIds` .
- Layout caches are invalidated automatically on filter or layer changes, reducing stale visualizations.
- Resetting overlays restores a clean state, including the filter set.

Risks & follow-ups

- Verify that `Set<string>` comparisons correctly detect changes; identical sets should not trigger unnecessary cache clears.
- Monitor performance during rapid filter updates to ensure cache clearing does not cause regressions.
- Run lint, tests, and production build to confirm integration stability.